





LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
J	-		BI	REVISED PER ECO-11-005140	05APR2011	RK

1. DOUBLE LOCK SHOULD BE SET TO THE PRE-ASSEMBLY POSITION WITHIN THE PLUG HOUSING WHEN SHIPPED TO THE CUSTOMER

1. ダブルロックは、仮係止状態で出荷される。



KYEING-2	GRAY	1473672-2
KYEING-1	NATURAL	1473672-1
KYEING	COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D. MATSUURA	20NOV01	TE TE Connectivity 025 4POSITION PLUG HOUSING		
DIMENSIONS: 単位: ㎜		CHK T. KOHNO	20NOV01			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD N. SAI	20NOV01			
一般公差 ±0.3		PRODUCT SPEC 108-5660				
0-PLC ±		APPLICATION SPEC		NAME	SIZE	CAGE CODE
1-PLC ±0.1		取付適用規格		名称	A3	00779
2-PLC ±0.01						DRAWING NO
3-PLC ±0.001						C=1473672
4-PLC ±0.0001						RESTRICTED TO
ANGLES ±1.00°						-
MATERIAL 材料	PBT	FINISH 仕上	-	WEIGHT	1.0 g	
CUSTOMER DRAWING				SCALE 尺度	5:1	SHEET 1
				OF	1	REV BI