



(非累積公差)
推奨基板取付け穴寸法 (コネクタ搭載面)
RECOMEND PC BOARD HOLL PATTERN (NOT ACCUMULATE TOLERANCE)
PC BOARD THICKNEES; 1.6 ± 0.1 (PC 基板厚; 1.6 ± 0.1)

- NOTES
- ① MATERIAL HOUSING: GLASS FILED POLYESTER
CONTACT: COPPER ALLOY
RETENTION LEG: COPPER ALLOY
 - ② FINISH (CONTACT AREA): 0.38 μm PdNi & Au PLATING OVER NICKEL
 - ③ FINISH (CONTACT AREA): 0.76 μm PdNi & Au PLATING OVER NICKEL
 - ④ FINISH (CONTACT): 2.0 μm MIN TIN PLATED OVER NICKEL
 - ⑤ FINISH (RETENTION LEG AND CONTACT TAIL): TIN-LEAD-PLATED OVER NICKEL
 - ⑥ FINISH (RETENTION LEG): TIN PLATED (CONTACT TAIL) OVER NICKEL

DIMENSIONS IN MILLIMETERS. DO NOT SCALE PRINT

KEYING LOCATION	KEYING NAME	FINISH	PART NO.
	XY	⑥ ④	3-178137-5
		⑥ ③	3-178137-3
	YY	⑥ ④	2-178137-5
		⑥ ③	2-178137-3
	XX	⑥ ④	1-178137-5
		⑥ ③	1-178137-3
		⑥ ②	1-178137-2

D	REVISED PER ECR-25-250788	F.Z	R.B	16 JAN 2025
C1	REVISED PER ECO-11-005030	RK	HMR	24 MAR 11
LTR	REVISION RECORD	DR	CHK	DATE

WIRE RANGE		INSULATION DIA		NAME	
mm ² (AWG -)		mmφ		DYNAMIC D-3100 3.81 X 7.62 PITCH(H) 6POS. HDR CONN. ASS'Y (KEY;XX,YY,XY)	
MATERIAL SEE NOTE 注記参照		FINISH SEE NOTE 注記参照		一般公差 (GENERAL TOLERANCE)	SIZE LOC NUMBER
DR. 1-JULY-'92 Y.TANAKA		DE. 1-JULY-'92 Y.TANAKA		10% : ±0.3 10% 30% : ±0.4 30% 100% : ±0.45 角度 : ±3'	A3 J C-178137
CHK. 6-JUL-'92 S.MANABE		APP. 6-JUL-'92 S.MANABE		SCALE	REV. SHEET
				2-1	D 1 OF 1