

USB 2.0 and 3.0 Connectors

Stewart Connector's USB 2.0 and USB 3.0 connectors are designed to meet the ever-growing demand for small yet reliable I/O connectors that comply to Universal Serial Bus standards.

The USB 3.0 connectors are fully backwards compatible with USB 2.0 and 1.0 connectors allowing for re-designs without having to update or change the mating connector. Stewart's line of USB connectors are known for being reliable, robust and versatile for all USB applications.



Features & Benefits

- High temperature plastic material used for reflow or wave soldering
- USB 2.0 and 3.0 connectors have 4 ports integrated into one PC board mount component that provides cost savings for any applications that require multiple USB ports
- All configurations are shielded
- Stacked, right angle, vertical orientations offered
- Through hole soldering
- Type A receptacle configuration for all USB offerings
- Plug and play capability that allows for hot pluggable insertion and ejection
- Space saving advantages



Applications

- Desktop and Laptop Computers
- Portable Storage Devices
- IOT Applications
- Printers and Scanners
- Audio and Diagnostic Applications
- POS Equipment
- Servers
- Game Ports

Operating temperature		-55°C to 85°C
Performance	USB 3.0	Deliver 5 Gbit/s
	USB 2.0	Can achieve 480 Mbit/s
Current rating	USB 3.0	1.8 A per contact
	USB 2.0	1.5 A per contact

Part Number	Connector Type	Ports	Orientation	Termination	Shielded
SS-52100-001	USB 2.0 - A	1	Horizontal	Solder	Yes
SS-52100-002	USB 2.0 - A	1	Vertical	Solder	Yes
SS-52100-003	USB 2.0 - A	2	Horizontal	Solder	Yes
SS-52100-004	USB 2.0 - A	4	Horizontal	Solder	Yes
SS-52000-001	USB 3.0 - A	1	Horizontal	Solder	Yes
SS-52000-002	USB 3.0 - A	1	Horizontal	Solder	Yes
SS-52000-003	USB 3.0 - A	2	Horizontal	Solder	Yes
SS-52000-004	USB 3.0 - A	1	Vertical	Solder	Yes
SS-52000-005	USB 3.0 - A	4	Horizontal	Solder	Yes



+1 717.235.7512
techhelp@belf.com

belfuse.com/stewart-connector