

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.




LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AG	53		0	RELEASED	25JAN06	JDP	JGH

D

C

B

A



- 1 MATERIAL:
EYELET - COPPER PER ASTM B 152
SPRING - BERYLLIUM COPPER PER ASTM B 194
- 2 TIN PLATE PER ASTM B 545, 0.00254 [.000100] MIN THK.
- 3 PACKAGED, 50,000 PER REEL
- 4 TO INSURE 1/2 OZ MIN RETENTION DO NOT EXCEED 0.10 [.004] DIFFERENCE IN PIN DIA WHEN CHANGING TO A SMALLER DIA PIN
- 5 PRODUCT IS OVALIZED FOR RETENTION IN THE P.C. BOARD. THE RECOMMENDED HOLE DIAMETER IS 1.32 [.052] MINIMUM, +0.08 [.003] MAX. PRIOR TO SOLDERING.
- 6 PACKAGED 10,000 PER REEL

2.54-4.32 [.100-.170]	$\phi 0.36 - \phi 0.66$ [$\phi .014 - \phi .026$]	TIN 2	TIN 2	6 1-5645956-1
2.54-4.32 [.100-.170]	$\phi 0.36 - \phi 0.66$ [$\phi .014 - \phi .026$]	TIN 2	TIN 2	3 5645956-1
LENGTH	DIA 4	SPRING	EYELET	PART NO.
PIN		FINISH		

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. POLIGNONE 25JAN06		tyco Electronics Tyco Electronics Corporation Harrisburg, PA 17105-3608								
		CHK J. HAVENER 25JAN06										
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. HAVENER 25JAN06		NAME						
		0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± 0.20[.008] 4 PLC ± - ANGLES ± ± -		PRODUCT SPEC		MINIATURE SPRING SOCKET ASSY SERIES 2 LONG WITHOUT SEALANT						
				108-14008								
		FINISH		APPLICATION SPEC		SIZE		CAGE CODE	DRAWING NO	RESTRICTED TO		
				114-26004		A2		00779	C=5645956	-		
MATERIAL		SEE TABLE		WEIGHT		-						
				CUSTOMER DRAWING		SCALE		1:1	SHEET	1 of 1	REV	0

5645956