

F

E

D



C

B

A

NOTES


1. 本製品は極数によって、ロック形状が変わりますのでご注意願います。
THE LOCK SHAPE OF THIS PRODUCT CHANGES ACCORDING TO THE NUMBER OF CIRCUIT.
2~5 CIRCUITS : フリクションロック FRICTION LOCK
6~15 CIRCUITS : インナーポジティブロック INNER POSITIVE LOCK
- △2 材料及び仕上げ(めっき仕様) : TABLE 1,2 参照
MATERIAL AND FINISHES : SEE TABLE 1 AND 2
3. 製品仕様書 : 2023960000 PS 000
PRODUCT SPECIFICATION:
4. 梱包形態 : SEE SHEET 4
PACKAGING INFORMATION:
- △5 嵌合相手 : 501330 シリーズ
MATES WITH:501330 SERIES
6. アプリケーション仕様書(コネクタ取扱い説明書) : 5013300000-AS 000
APPLICATION SPECIFICATION(CONNECTOR MANUAL):
7. ソルダーピン及びネイルの平坦度:0.1 MAX.
SOLDER PIN AND NAIL COPLANARITY: 0.1 MAX.
- △8 偶数極に適用
APPLY FOR EVEN CIRCUIT
9. その他金めっき厚品及び錫めっき品は以下の図面をご参照ください。
PLEASE REFER TO THE FOLLOWING DRAWING
FOR OTHER GOLD PLATING VERSION AND TIN PLATING VERSION.



PLATING	PLATING THICKNESS [micro-meter MIN.]	SERIES No.	DRAWING No.
TIN	1.0	501568	5015680000-SD PSD 000
GOLD	0.38	203558	2035580000-SD PSD 000
	0.76	203559	2035590000-SD PSD 000

△2 TABLE 1

番号 NO.	部品 PART	材質 MATERIAL	
①	ウエハー WAFER	ポリアミド(PA), UL94V-0, 色 : SEE SHEET 6 POLYAMIDE(PA), UL94V-0, COLOR : SEE SHEET 6	
②	ソルダーピン SOLDER PIN	リン青銅 PHOSPHOR BRONZE	
		接点部 CONTACT AREA	金めっき : 0.1 MICRO-METER MIN. GOLD PLATING
		テール部 TAIL AREA	金めっき : 0.05 MICRO-METER MIN. GOLD PLATING
		下地めっき UNDER PLATING	ニッケルめっき : 1.27 MICRO-METER MIN. NICKEL
③	ネイル NAIL	黄銅 BRASS	
		テール部 TAIL AREA	錫めっき : 1.0 MICRO-METER MIN. MATTE TIN PLATING
		下地めっき UNDER PLATING	ニッケルめっき : 1.0 MICRO-METER MIN. NICKEL



6.2	4.0	7.0	5
5.2	3.0	6.0	4
4.2	2.0	5.0	3
3.2	1.0	4.0	2
C	B	A	極数 CIRCUIT SIZE

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC:		molex			
mm	NTS						
GENERAL TOLERANCES (UNLESS SPECIFIED)							
ANGULAR TOL	± 3.0 °						
4 PLACES	± 0.2	EC NO: 794263					
3 PLACES	± 0.2	DRWN: MIKEDA01		2023/06/27			
2 PLACES	± 0.2	CHK'D: SAKIYAMA		2024/09/26			
1 PLACE	± 0.2	APPR: AIDA		2024/09/27			
0 PLACES	± 0.2	INITIAL REVISION:					
		DRWN: AISHIKAWA		2019/04/02			
		APPR: KOMURAKAMI		2019/04/05			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
			A3-SIZE	202396	SEE SHEET 6		1 OF 6

EC NO: 794263
DRWN: MIKEDA01
CHK'D: SAKIYAMA
APPR: AIDA

2023/06/27
2024/09/26
2024/09/27

INITIAL REVISION:
DRWN: AISHIKAWA
APPR: KOMURAKAMI

2019/04/02
2019/04/05

DOCUMENT NUMBER
2023960000-SD

DOC TYPE
PSD

DOC PART
000

REVISION
D


PICO-CLASP 1.0 W/B
SINGLE ROW RA SMT INNER LOCK GOLD PLATING
0.1 MICRO-METER

PRODUCT CUSTOMER DRAWING

NOTES

10. 梱包数量
- 2-5 CIRCUIT: 1700個/リール
- 6-15 CIRCUIT: 1300個/リール
- NUMBER OF CONNECTORS
- 2-5 CIRCUIT : 1700 PIECES/REEL
- 6-15 CIRCUIT : 1300 PIECES/REEL

11. リードテープ長さ
- LEAD TAPE LENGTH





12. トップテープの剥離強度はIEC60286-3に準拠。
- TOP TAPE PEELING FORCE IS DEFINED BY IEC60286-3.
- △13 2~5極品は乾燥剤入り、ハイバリア梱包による納品となります。
- 2~5 CIRCUITS IS DELIVERED IN A HIGH BARRIER PACKAGING WITH DESICCANT.

14. 梱包仕様書 : 2023969200 PS 200
- PACKAGE SPECIFICATION:

- △15 発注番号 : SHEET 6 参照
- ORDER No. : PLEASE REFER TO SHEET 6 FOR PRODUCT LIST.

202396 - ** * *


極数	ハウジングカラー	製品識別番号
CIRCUIT SIZE	HOUSING COLOR	IDENTIFICATION NUMBER
	0:NATURAL(BEIGE)	7:EMBOSSED PACKAGE



番号 NO.	部品 PART	材質 MATERIAL
④	リール REEL	ポリスチレン(PS) <リサイクル材を含む> POLYSTYRENE(PS) <RECYCLE MATERIAL CONTAINED>

DOCUMENT STATUS	P1	RELEASE DATE	2024/09/27	10:55:20
-----------------	----	--------------	------------	----------

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
DIMENSION UNITS		SCALE		CURRENT REV DESC:			molex				
mm		NTS									
GENERAL TOLERANCES (UNLESS SPECIFIED)				PICO-CLASP 1.0 W/B SINGLE ROW RA SMT INNER LOCK GOLD PLATING 0.1 MICRO-METER							
ANGULAR TOL ± 3.0 °											
4 PLACES		± 0.2		EC NO: 794263			PRODUCT CUSTOMER DRAWING				
3 PLACES		± 0.2		DRWN: MIKEDA01 2023/06/27							
2 PLACES		± 0.2		CHK'D: SAKIYAMA 2024/09/26							
1 PLACE		± 0.2		APPR: AIDA 2024/09/27			DOCUMENT NUMBER 2023960000-SD				
0 PLACES		± 0.2		INITIAL REVISION: DRWN: AISHIKAWA 2019/04/02 APPR: KOMURAKAMI 2019/04/05						DOC TYPE PSD	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		DOC PART 000		REVISION D	
						A3-SIZE		SHEET NUMBER 4 OF 6			
				SERIES 202396		MATERIAL NUMBER SEE SHEET 6		CUSTOMER			



17.3	14.2	32	15
16.3			14
15.3			13
14.3	11.5	24	12
13.3			11
12.3			10
11.3			9
10.3			8
9.3			7
8.3	7.5	16	6
7.3			5
6.3			4
5.3			3
4.3			2
G	コネクタ中心位置 F SENER OF CONNECTOR	エンボステープ幅 E WIDTH OF TAPE	極数 CIRCUIT SIZE

番号 NO.	部品 PART	材質 MATERIAL
⑤	キャリアテープ CARRIER TAPE	ポリプロピレン(PP)、その他 POLYPROPYLENE(PP), etc
⑥	トップテープ TOP TAPE	ポリエチレン(PE)、その他 POLYETHYLENE(PE), etc

DOCUMENT STATUS	P1	RELEASE DATE	2024/09/27	10:55:20
-----------------	----	--------------	------------	----------

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		CURRENT REV DESC:			molex		
mm		NTS							
GENERAL TOLERANCES (UNLESS SPECIFIED)							PICO-CLASP 1.0 W/B		
ANGULAR TOL ± 3.0 °							SINGLE ROW RA SMT INNER LOCK GOLD PLATING		
4 PLACES ± 0.2							0.1 MICRO-METER		
3 PLACES ± 0.2				EC NO: 794263			PRODUCT CUSTOMER DRAWING		
2 PLACES ± 0.2				DRWN: MIKEDA01 2023/06/27					
1 PLACE ± 0.2				CHK'D: SAKIYAMA 2024/09/26					
0 PLACES ± 0.2				APPR: AIDA 2024/09/27			DOCUMENT NUMBER		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				INITIAL REVISION:			2023960000-SD		
				DRWN: AISHIKAWA 2019/04/02			DOC TYPE		
				APPR: KOMURAKAMI 2019/04/05			DOC PART		
THIRD ANGLE PROJECTION				DRAWING		SERIES		REVISION	
				A3-SIZE		202396		D	
						MATERIAL NUMBER		CUSTOMER	
						SEE SHEET 6		SHEET NUMBER	
								5 OF 6	

10	9	8	7	6	5	4	3	2	1