



**Pushing Performance**  
Since 1945

## Han Modular frame 6 housing 2 module a-b



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 09 14 006 0313                                                                |
| Specification      | Han Modular frame 6 housing 2 module a-b                                      |
| HARTING eCatalogue | <a href="https://harting.com/09140060313">https://harting.com/09140060313</a> |

### Identification

|                              |                                                                                                                                        |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Category                     | Accessories                                                                                                                            |
| Series                       | Han-Modular®                                                                                                                           |
| Type of accessory            | Hinged frame                                                                                                                           |
| Description of the accessory | for 2 modules<br>a ... b                                                                                                               |
| Features                     | Conductor cross-section PE (power side) 4 ... 10 mm <sup>2</sup><br>Conductor cross-section PE (signal side) 1 ... 2.5 mm <sup>2</sup> |

### Version

|      |     |
|------|-----|
| Size | 6 B |
|------|-----|

### Technical characteristics

|                          |                                          |
|--------------------------|------------------------------------------|
| Stripping length         | 8 ... 10 mm                              |
| Tightening torque        | 0.8 Nm PE screw M3<br>1.2 Nm PE screw M4 |
| Recommended screw driver | Slotted 0.6 x 3.5<br>PH2                 |
| Limiting temperature     | -40 ... +125 °C                          |
| Mating cycles            | ≥500                                     |

### Material properties

|                 |                                                        |
|-----------------|--------------------------------------------------------|
| Material        | Zinc die-cast                                          |
| RoHS            | compliant with exemption                               |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status      | compliant with exemption                               |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| China RoHS                           | 50                                   |
| REACH Annex XVII substances          | Not contained                        |
| REACH ANNEX XIV substances           | Not contained                        |
| REACH SVHC substances                | Yes                                  |
| REACH SVHC substances                | Lead                                 |
| ECHA SCIP number                     | 564b7d75-7bf6-4cfb-acb1-2168eb61b675 |
| California Proposition 65 substances | Yes                                  |
| California Proposition 65 substances | Lead                                 |

## Specifications and approvals

|                |                       |
|----------------|-----------------------|
| Specifications | IEC 60664-1           |
|                | IEC 61984             |
|                | IEC 61373 Category 2  |
| UL / CSA       | UL 1977 ECBT2.E235076 |
| Approvals      | DNV GL                |

## Commercial data

|                                |                                                         |
|--------------------------------|---------------------------------------------------------|
| Packaging size                 | 2                                                       |
| Net weight                     | 40 g                                                    |
| Country of origin              | Germany                                                 |
| European customs tariff number | 85389099                                                |
| GTIN                           | 5713140020375                                           |
| eCl@ss                         | 27440206 Module carrier frame for industrial connectors |
| ETIM                           | EC002312                                                |
| UNSPSC 24.0                    | 39121421                                                |