

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-40 °C TO +120 °C ⁽²⁾		STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C ⁽¹⁾
	CURRENT	30 A		STORAGE HUMIDITY RANGE	RELATIVE HUMIDITY 85% MAX
	VOLTAGE	600 V AC/DC			(NOT DEWED)
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	x x
MARKING		CONFIRMED VISUALLY.			x x
ELECTRICAL CHARACTERISTICS					
CONTACT RESISTANCE		10 A DC.		3 mΩ MAX.	x -
CONTACT RESISTANCE		20 mV AC MAX, 10 mA(DC OR 1000Hz)		3 mΩ MAX.	x -
MILLIVOLT LEVEL METHOD					
INSULATION RESISTANCE		1000 V DC.		100 MΩ MIN.	x -
VOLTAGE PROOF		2200 V AC FOR 1 min.		NO BREAKDOWN	x -
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 5 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x - x -
VIBRATION		FREQUENCY 20 TO 400Hz (43.1m/s ²) SWEEP TIME 3min.(ROUND TRIP) AT 3h FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 7ΩMIN , 1μs MIN. ② CONTACT RESISTANCE: 5 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x - x - x -
LOCK STRENGTH		MEASURE BREAK STRENGTH OF THE LOCK BY PULLING THE CONNECTOR IN THE MATING DIRECTION.		110N MIN. ②	x -
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)		EXPOSED AT 60 °C, 90 ~ 95 %, 96 h.		① CONTACT RESISTANCE: 5 mΩ MAX. ② INSULATION RESISTANCE:100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x - x - x -
RAPID CHANGE OF TEMPERATURE		TEMPERATURE- 40 →ROOM TEMP →120°C→ ROOM TEMP TIME 30 → 5 → 30 → 5 min UNDER 100 CYCLES.		① CONTACT RESISTANCE: 5 mΩ MAX. ② INSULATION RESISTANCE:100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x - x - x -
DRY HEAT		EXPOSED AT 125°C, 300 h.		① CONTACT RESISTANCE: 5 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x - x -
COLD		EXPOSED AT -40°C , 120 h.		① CONTACT RESISTANCE: 5 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	x - x -
RESISTANCE TO SO ₂ GAS		EXPOSED IN 25 ppm AT 75% MIN FOR 96h.		CONTACT RESISTANCE: 5 mΩ MAX.	x -
RESISTANCE TO SOLDERING HEAT		SOLDERED AT SOLDER TEMPERATURE 260°C FOR 10s.		NO PLATING PEELING OF THE TERMINALS, MELTINGS OF HOUSINGS.	- -
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE 245°C FOR 3s.		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSSED.	- -
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
②	5	DIS-T-00024017	AN. SAIKI	TY. MOGI	20250519
REMARK			APPROVED	HK. UMEHARA	20180928
(NOTE1) "STORAGE" means a long-term storage state for the unused product.			CHECKED	AH. EDASHIGE	20180928
(NOTE2) Include the temperature rising by current. ②			DESIGNED	TS. SHIMIZU	20180928
			DRAWN	DS. HIROWATARI	20180926
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-382042-00-00
HRS	SPECIFICATION SHEET		PART NO.	HVH-280-2P/S-R	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0778-0705-0-00	② 1/1