

APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +105°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60°C (NOTE3)						
	OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)	STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3)						
	APPLICABLE CONNECTOR	DF62B-*EP-2.2C(##) DF62P-*EP-2.2C(##)	VOLTAGE	AC/DC 250V						
	APPLICABLE CABLE	AWG 22	CURRENT	AWG 22 : 3A/pin						
	INSULATION DIAMETER 	φ 1.26 ~ φ 1.30 mm								
SPECIFICATIONS										
ITEM		TEST METHOD		REQUIREMENTS						
CONSTRUCTION										
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.						
MARKING		CONFIRMED VISUALLY.								
ELECTRIC CHARACTERISTICS										
CONTACT RESISTANCE		20mV MAX, 1mA (DC or 1000Hz).		30 mΩ MAX.						
MECHANICAL CHARACTERISTICS										
MECHANICAL OPERATION		30 TIMES INSERTION AND EXTRACTION.		①CONTACT RESISTANCE: 30 mΩ MAX. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.						
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.		①NO ELECTRICAL DISCONTINUITY OF 1 μ s. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.						
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES EACH FOR 3 BOTH AXIAL DIRECTIONS.		①NO ELECTRICAL DISCONTINUITY OF 1 μ s. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.						
ENVIRONMENTAL CHARACTERISTICS										
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2°C , 90 TO 95 %, 96 h. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)		①CONTACT RESISTANCE: 30 mΩ MAX. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.						
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55°C→ +85°C TIME 30min→ 30min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE TANK IS 2~3 min) (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)		①CONTACT RESISTANCE: 30 mΩ MAX. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.						
NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT. NOTE2: NO CONDENSING. NOTE3: APPLY TO THE PACKAGED AND UNUSED PRODUCT. 										
COUNT		DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE					
 2		DIS-H-00022584	TS. KUMAZAWA	SZ. ONO	20250306					
REMARKS Unless otherwise specified, refer to IEC 60512.			APPROVED	KI. AKIYAMA	20140426					
			CHECKED	KI. AKIYAMA	20140426					
			DESIGNED	TS. KUMAZAWA	20140425					
			DRAWN	TS. KUMAZAWA	20140425					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-344684-00-00						
	SPECIFICATION SHEET		PART NO.	DF62-EP22PCF						
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0544-0523-4-00	 1/1					