

5

4

3

2

1

Description: See Table I

Part No: See Table I

Application: See Table1

Crimp Tool: N/A




Impedance: N/A

Frequency Range: N/A

Material: Contact Copper alloy
Screw Steel

RoHS Compliance: Yes

Technical Detail: N/A



2 x MALE(FEMALE) 9 PIN D-SUB CONNECTOR

受控 CONTROLLED DOCUMENT

编号 P/N	30-9530	版本 Rev	01	日期 Rel'd Date	DEC 17,09
-----------	---------	-----------	----	------------------	-----------

TABLE I

PIN	DESCRIPTION	W1	W	L1	L	Pin quantities	Hex standoff quantities
30-9530	SLIM GENDER CHANGER DB9 F/F	6.350	12.700	24.892	31.750	9	2
30-9531	SLIM GENDER CHANGER DB9 MM	6.350	12.700	24.892	31.750	9	0
30-9532	SLIM GENDER CHANGER DB15 F/F	6.350	12.700	24.892	31.750	15	2
30-9533	SLIM GENDER CHANGER DB15 MM	6.350	12.700	24.892	31.750	15	0
30-9534	SLIM GENDER CHANGER DB 25 F/F	5.842	12.954	46.990	53.340	25	2
30-9535	SLIM GENDER CHANGER DB 25 MM	5.842	12.954	46.990	53.340	25	0

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY	DATE
DECIMALS	mm	LINDA.WU	11-12-09
X	+ 0.5	CHECKED BY	DATE
X.X	+ 0.3	LINDA.WU	11-12-09
X.XXX	+ 0.2	APPROVED BY	DATE
ANGLES	+ 0.5°	THOMAS	11-12-09
		U/M	mm

THIS DRAWING WAS PRODUCED BY COMPUTER,
DO NOT SCALE DRAWING OR UPDATE MANUALLY.DRAWING NO.
30-9530-CUST(SEE TABLE I)

REVISIONS

01	OFFICIAL RELEASE	L	L	T	H	Betty	2009.12.1
	11-12-09						L 10.28.07 +0800

CUSTOMER COPY

TITLE
DBX, M(F)/M(F) GENDER CHANGER

SHEET 1 OF 1 DRAWING NO. 30-9530-CUST (SEE TABLE I) SIZE A