


Jun.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- Notes 1. Per tray : 64 Pieces.
 2. Refer to the technical specification (ETAP-H0816-00) for the packing type.
 3. UL(File No. E52653)
 C-UL(File No. E52653)
 TUV (Certificate No. R50400864) authorization article.



Lot No. is displayed in one of the two locations.

1	PBT	Red. 94-V0	3	PS	White
2	Copper Alloy		2	Copper Alloy	Contact Area : Au Plating 0.2μm min LEAD Area : Tin Plating 1μm min Under Plating : Ni Plating 1μm min
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 3	DESCRIPTION OF REVISIONS DIS-H-00012301	DESIGNED TS.MIYAKI
HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA 20171011	DRAWING NO. EDC-379290-50-00		
		CHECED : ST. WADA 20171011	PART NO. DF60FR-3P-10.16DSA(50)		
		DESIGNED : TT. OHSAKO 20171011	CODE NO. CL0680-4004-0-50		
		DRAWN : TT. OHSAKO 20171011	1/1		
FORM HC0011-5-7_AN					