

Jun.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Applicable standard					
Rating	Operating temperature range	-40 °C to +90 °C (90 %RH Max.)	Storage temperature range	-20 °C to +70 °C (90 %RH Max.)	
	Power	-- W	Characteristic impedance	50 Ω (0 to 30 GHz)	
	Peculiarity	----	Applicable cable	----	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
General examination	Visually and by measuring instrument.		According to drawing.	X	X
Marking	Confirmed visually.			--	--
ELECTRICAL CHARACTERISTICS					
Contact resistance	10 mA Max.(DC or 1000 Hz)		Center contact 60 mΩ Max.	X	--
			Outer contact 20 mΩ Max.	X	--
Insulation resistance	100 V DC.		500 MΩ Min.	X	--
Withstanding voltage	200 V AC for 1 min. current leakage 2 mA Max.		No flashover or breakdown.	X	--
② Voltage standing wave ratio	Frequency 0 to 15 GHz.		VSWR 1.4 Max.	X	--
	Frequency 15 to 20 GHz.		VSWR 1.5 Max.		
	Frequency 20 to 30 GHz.		VSWR 1.6 Max.		
Insertion loss	Frequency - to - GHz.		--- dB Max.	--	--
MECHANICAL CHARACTERISTICS					
Contact insertion and extraction forces	φ --- with steel gauge.		Insertion force --- N Max.	--	--
			Extraction force --- N Min.	--	--
Insertion and extraction forces	Measured with an applicable connector.		Insertion force 30 N Max.	X	--
			Extraction force 3 to 25 N	X	--
Mechanical operation	20 times insertion and extractions.		1)Contact resistance: Center contact 65 mΩ Max. Outer contact 25 mΩ Max.	X	--
Vibration	Frequency 10 to 100 Hz single amplitude 1.5 mm, 59 m/s ² over 5 cycles in 3 directions.		1)No electrical discontinuity of 1 μs.	X	--
			2)No damage, cracks or looseness of parts.		
Shock	735 m/s ² directions of pulse 11 ms at 3 times in 6 directions.			X	--
Cable clamp strength (Against cable pull)	Using a pulling tester, pull the cable axially at a rate of -- mm/min. and record the strength at which the cable or connector breaks.		-- N Min.	--	--
ENVIRONMENTAL CHARACTERISTICS					
Damp heat	Exposed at +40 °C, 95 % total -- cycles.(96 h)		1)Insulation resistance: 10 MΩ Min. (at high humidity) 2) Insulation resistance: 500 MΩ Min. (when dry) 3)No damage, cracks or looseness of parts.	X	--
Rapid change of temperature	Temperature -40 → - → +90 → - °C Time 30 → 3 → 30 → 3 min. Under 5 cycles.		No damage, cracks or looseness of parts.	X	--
	Count	Description of revisions	Designed	Checked	Date
⚠	1	DIS-D-00004497	YJ.HAGA	NK.NINOMIYA	20191023
Remark			Approved	KH.IKEDA	20171125
1. The quantity of this product is 20,000 connectors per reel.			Checked	MH.TSUCHIDA	20171125
② Measured with an applicable inspection adapter.			Designed	YJ.HAGA	20171125
Unless otherwise specified, refer to IEC 60512.			Drawn	YJ.HAGA	20171125
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test		Drawing No.	ELC-375224-90-00	
HRS	SPECIFICATION SHEET		Part No.	C.FL-R-SMT-1(90)	
	HIROSE ELECTRIC CO., LTD.		Code No.	CL331-2200-0-90	⚠ 1/1