




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.32 – 1.04 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Dimensions

Wire Size	.32 – 1.04 mm²
Product Length	27 mm[1.063 in]
Compatible Insulation Diameter Range	2.31 mm[.091 in]
Terminal Material Thickness	.36 mm[.014 in]

Packaging Features

Packaging Method	Strip/Reel
------------------	------------



Packaging Quantity	3000
Product Type Features	
Insertion Force	Normal
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
Other	
EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single
Electrical Characteristics	
Voltage Rating	250 V
Termination Features	
Product Terminates To	Wire & Cable
Mechanical Attachment	
Locking Lance Height	1.5 mm[.06 in]
Wire Insulation Support	With
Mating Retention Type	Locking Lance
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2150035-2
OCEAN_2.0_Applicator-E-080F130F-REA

TE Part # 7-2150035-7
OCEAN_2.0_SPARE_PART_KIT-080F130F

TE Part # 144838-2
FF 5MM TAB 22-17 AWG .031 PTPB

TE Part # 1-1241857-5
5POS. FASTIN-FASTON* TAB HSG, RAST5

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(207)

Insertion & Extraction Tools(2)

PCB Terminals(2)

Quick Disconnects(250)

Customers Also Bought


TE Part #1217073-1
CONT AMVAR 125 BLADE 020 TPBR

TE Part #3-293041-2
FASTIN FASTON 250 TAB 0.35-1.00 MM2 PTPBR


TE Part #1217071-1
CONTACT, BLADE 125 20-16 AWG TPBR

TE Part #1394430-3
MAG MATE CONT. 5D





TE Part #1-172233-9
2P MINI UNIV FREE HANG BLACK



TE Part #1-293008-1
3 POS. FASTIN-FASTON CONN. TAB HOUSING R



TE Part #925575-1
STC REC 6.3 Contact SRC Sn

TE Part #1394429-6
TP 1394429-2 wh 2-703453-0 PP no Ni PLTN

Documents

Product Drawings

FF 250 TAB 0.35-1.0MM2 TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_293041-2_C_c-293041-2-c.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_293041-2_C_c-293041-2-c.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_293041-2_C_c-293041-2-c.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

FASTIN-FASTON* Connectors, 6.3 mm series TAB CONTACT.

Application Specification

Agency Approvals

UL Report

English