



**Part Number :** [2137192081](#)

**Product Description :** 2.00mm Pitch, Micro-Lock Plus Plug Crimp Housing, Single Row, 8 Circuits, UL 94V-0, Black

**Series Number :** 213719

**Status :** Active

**Product Category :** Connector Housings



---

## Documents & Resources

### Drawings

[2137192081\\_sd.pdf](#)

### 3D Models and Design Files

[2137192081.dxf](#)

[2137192081.pdf](#)

[2137192081\\_stp.zip](#)

### Specifications

[5055700001-A03.pdf](#)

[213719200-SPK-200.pdf](#)

[5055700003-PS-000.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Connector Housings
Series	213719
Description	2.00mm Pitch, Micro-Lock Plus Plug Crimp Housing, Single Row, 8 Circuits, UL 94V-0, Black
Application	Power, Wire-to-Wire
Product Name	Micro-Lock Plus
UPC	193264756551

### Agency

UL	E29179
----	--------

### Physical

Circuits (maximum)	8
Color - Resin	Black
Flammability	94V-0
Gender	Plug
Glow-Wire Capable	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Polyamide
Net Weight	2042.260/mg
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.00mm

Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +105°C

---

## Mates With / Use With

### Mates with Part(s)

Description	Part Number
2.00mm Pitch, Micro-Lock Plus Single Row Receptacle Housings	<u>505570</u>

### Use with Part(s)

Description	Part Number
Micro-Lock Plus Male Crimp Terminals	<u>213720</u>

---