

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [35718-1510](#)
Status: **Active**
Overview: [Quick-Disconnect Terminals](#)
Description: 4.75mm Tab Slip-On Terminal, Quick Disconnect, Female, 0.50mm Tab Thickness, Wire Range 10-14 AWG (5.26-2.08mm²), Post-Tin Plated

Documents:
[Drawing \(PDF\)](#) [Packaging Specification PK-35718-001 \(PDF\)](#)
[Product Specification PS-35703-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR95446
UL E92853

General

Product Family Quick Disconnects
Series [35718](#)
Crimp Quality Equipment Yes
Insulated No
Overview [Quick-Disconnect Terminals](#)
Product Name Slip-On
Type Quick Disconnect
UPC 800753199552

Physical

Barrel Type Open
Gender Female
Glow-Wire Compliant No
Insulation None
Lock to Mating Part Yes
Material - Metal Brass
Material - Plating Mating Tin
Material - Plating Termination Tin
Net Weight 0.561/g
Orientation Straight
Packaging Type Reel
Plating min - Mating 1.016µm
Plating min - Termination 1.016µm
Polarized to Mating Part No
Tab Thickness 0.51mm
Tab Width 4.75mm
Temperature Range - Operating -40°C to +105°C
Termination Interface: Style Crimp or Compression
Wire Insulation Diameter 4.40-5.30mm max.
Wire Size AWG 10, 12, 14
Wire Size mm² 2.08 - 5.26


Electrical

Voltage - Maximum 250V

Material Info

Reference - Drawing Numbers

Packaging Specification PK-35718-001
Product Specification PS-35703-001
Sales Drawing SD-35718-15*0



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[35718Series](#)

Use With
4.75mm Tab

This document was generated on 12/12/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION