




注記 NOTES

1. 使用材料 MATERIAL

ハウジング : 46ナイロン、UL94V-0
HOUSING 46NYLON

アクチュエータ : PPS、UL94V-0
ACTUATOR

ターミナル : リン青銅(±0.2) ニッケル下地・錫ピスマスメッキ
TERMINAL PHOS-BRO,TIN-BITHMUS OVER NICKEL PLATED

金具 : リン青銅(±0.2) ニッケル下地、錫メッキ
FITTING NAIL PHOS-BRO,TIN OVER NICKEL PLATED

2. エンボステープ梱包時は、アクチュエータがロックした状態とする。
IN THE PACKAGE,ACTUATOR OF PART NO.52746-**19 SHOULD BE LOCKED.

3. ソルダータール半田付け面のズレ量、及び金具半田付け面のズレ量は、基準面 H に対し上方向 0.1MAX. 下方向 0.15MAX. とする。
MISALIGNMENT OF SOLDER TAILS AND FITTING NAILS FROM H
UPPER DIRECTION: 0.1MAX. , LOWER DIRECTION: 0.15MAX.

4. 偶数極に適用。
APPLY FOR EVEN CIRCUIT.


5. パターンはくり止め用金具
FITTING NAIL FOR PREVENTION OF PEELING OF P.C.B. PATTERN.

6. 本製品は 52746-**17 の鉛フリー品です。
THIS PRODUCT IS LEAD FREE OF 52746-**17


7. R0.3 は、FPC の導体部にかからないこと。
R0.3 MUST NOT BE OVERLAPPED TO PATTERN OF FPC.

16.1	14.3	10.65	9.5	52746-2070	52746-2019	20
15.6	13.8	10.15	9.0	-1970	-1919	19
15.1	13.3	9.65	8.5	-1870	-1819	18
14.6	12.8	9.15	8.0	-1770	-1719	17
14.1	12.3	8.65	7.5	-1670	-1619	16
13.6	11.8	8.15	7.0	-1570	-1519	15
13.1	11.3	7.65	6.5	-1470	-1419	14
12.6	10.8	7.15	6.0	-1370	-1319	13
12.1	10.3	6.65	5.5	-1270	-1219	12
11.6	9.8	6.15	5.0	-1170	-1119	11
11.1	9.3	5.65	4.5	-1070	-1019	10
10.6	8.8	5.15	4.0	-0970	-0919	9
10.1	8.3	4.65	3.5	-0870	-0819	8
9.6	7.8	4.15	3.0	-0770	-0719	7
9.1	7.3	3.65	2.5	-0670	-0619	6
8.1	6.3	2.65	1.5	52746-0470	52746-0419	4
D	C	B	(A)	EMBOSSSED TAPE	MATERIAL NO.	極数
				ORDER No. オーダー番号	CIRCUITS	



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																	
DIMENSION UNITS		SCALE		CURRENT REV DESC:				molex 0.5 FPC CONN. ZIF SMT R/A -LEAD FREE-									
mm		NTS															
GENERAL TOLERANCES (UNLESS SPECIFIED) ANGULAR TOL ± 3.0 ° 4 PLACES ± 0.2 3 PLACES ± 0.25 2 PLACES ± 0.3 1 PLACE ± 0 PLACES ± DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				EC NO: 758488				PRODUCT CUSTOMER DRAWING									
				DRWN: RAJAGN 2023/03/17													
				CHK'D: HSHIMOYAMA 2023/08/03													
				APPR: YNAITO 2023/08/03				DOCUMENT NUMBER				DOC TYPE		DOC PART		REVISION	
				INITIAL REVISION:				SD-52746-028				PSD		001		G	
				DRWN: MNABEI 2008/06/27				MATERIAL NUMBER				CUSTOMER				SHEET NUMBER	
APPR: NUKITA 2008/06/30				SEE TABLE				GENERAL MARKET				1 OF 2					
THIRD ANGLE PROJECTION				DRAWING		SERIES											
				A3-SIZE		52746											



適合FPC推奨寸法
APPLICABLE FPC
RECOMMENDED DIMENSION.
(仕上がり厚さ: $0.3^{+0.05}$)
(THICKNESS: $0.3^{+0.05}$)





適合FFC推奨寸法
APPLICABLE FFC
RECOMMENDED DIMENSION.
(仕上がり厚さ: $0.3^{+0.05}$)
(THICKNESS: $0.3^{+0.05}$)




参考基板レイアウト (マウント面)

RECOMMENDED P.C.BOARD
PATTERN DIMENSION (REF.)
(MOUNTING SIDE)



FPC構成推奨仕様

RECOMMENDED STRUCTURE OF FPC



FFC構成推奨仕様

RECOMMENDED STRUCTURE OF FFC

FPCについて:

打抜き方向は導体側から補強板を推奨致します。
補強フィルム材質はポリイミドを推奨致します。
接着剤は熱硬化接着剤を推奨致します。

ABOUT FPC:

RECOMMENDED PUNCHER DIRECTION : FROM CONDUCTOR SIDE TO STIFFENER BOARD SIDE.

RECOMMENDED MATERIAL :


STIFFENER FILM : POLYIMIDE

BONDING AGENT : THERMOSETTING BONDING AGENT

DOCUMENT STATUS	P1	RELEASE DATE	2023/08/03	11:20:34
-----------------	----	--------------	------------	----------


GENERAL TOLERANCES (UNLESS SPECIFIED)	
10 ^{UNDER}	±0.2
10 ^{OVER} 30 ^{UNDER}	±0.25
30 ^{OVER}	±0.3
ANGULAR	±3 °

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										
DIMENSION UNITS		SCALE		CURRENT REV DESC:		molex				
mm		NTS								
GENERAL TOLERANCES (UNLESS SPECIFIED)		ANGULAR TOL ± 3.0°		EC NO: 758488		0.5 FPC CONN. ZIF SMT R/A -LEAD FREE-				
		4 PLACES ± 0.2		DRWN: RAJAGN 2023/03/17						
		3 PLACES ± 0.25		CHK'D: HSHIMOYAMA 2023/08/03						
		2 PLACES ± 0.3		APPR: YNAITO 2023/08/03		PRODUCT CUSTOMER DRAWING				
		1 PLACE ±		INITIAL REVISION:		DOCUMENT NUMBER		DOC TYPE		DOC PART
0 PLACES ±		DRWN: MNABEI 2008/06/27		SD-52746-028		PSD		001	G	
APPR: NUKITA 2008/06/27		THIRD ANGLE PROJECTION		DRAWING	SERIES	MATERIAL NUMBER		CUSTOMER		SHEET NUMBER
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				A3-SIZE 52746		SEE SHEET-1		GENERAL MARKET		2 OF 2



注記 NOTES

- 1. 製品番号 52746-**19 の梱包状態はアクチュエータがロックした状態とする。
詳細寸法については図面 SD-52746-028 を参照下さい。
IN THE PACKAGE,ACTUATOR OF PART NO.52746-**19 SHOULD BE LOCKED
RE DETAILED DIMENSIONS,SEE SD-52746-028.
- 2. 梱包数量：1000個／リール
NUMBER OF CONNECTORS:1000PCS／REEL
- 3. リードテープ長さ LEAD TAPE LENGTH
トップテープ リーダー部 175 ±25
トップテープ 未接着部 25 ±5
TOP TAPE LEADER PART TOP TAPE NON-BONDED PART
引き出し方向 PULL OUT DIRECTION
リーダー部 (空部) LEADER PART (EMPTY) 120 ±20
部品挿入部 COMPONENT SUPPLIER
末端部 (空部) TAIL PART (EMPTY) 150 ±40
- 4. 材料 キャリアテープ：ポリプロピレン (PP)
トップテープ：PET, PE, PEF
リール：ポリスチレン (PS) <リサイクル材を含む>
MATERIAL CARRIER TAPE:POLYPROPYLENE
TOP TAPE:PET,PE,PEF
REEL:POLYSTYREN(PS)
<RECYCLE MATERIAL CONTAINED>
- 5. 本製品は 52746-**90 の鉛フリー品です
THIS PRODUCT IS LEAD FREE OF 52746-**90
- 6.本製品は乾燥剤入り、ハイバリア梱包仕様である。
THIS PRODUCT IS HIGH BARRIER PACKAGE WITH DESICCANT.



24	29.4	25.4	17.4	10.8	16.4	52746-2070	20
			16.9	10.3	15.9	↑ - 1970	19
			16.4	9.8	15.4	↑ - 1870	18
			15.9	9.3	14.9	↑ - 1770	17
			15.4	8.8	14.4	↑ - 1670	16
			14.9	8.3	13.9	↑ - 1570	15
			14.4	7.8	13.4	↑ - 1470	14
			13.9	7.3	12.9	↑ - 1370	13
			13.4	6.8	12.4	↑ - 1270	12
			12.9	6.3	11.9	↑ - 1170	11
			12.4	5.8	11.4	↑ - 1070	10
			11.9	5.3	10.9	↑ - 0970	9
			11.4	4.8	10.4	↑ - 0870	8
			10.9	4.3	9.9	↑ - 0770	7
10.4	3.8	9.4	↓ - 0670	6			
16	21.4	17.4		2.8	8.4	52746-0470	4
キャリアテープ幅 CARRIER TAPE WIDTH	E	D	(C)	(B)	(A)	MATERIAL NO.	極数 CIRCUITS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

mm

NTS

GENERAL TOLERANCES (UNLESS SPECIFIED)

ANGULAR TOL ± °

4 PLACES ±

3 PLACES ±

2 PLACES ±

1 PLACE ±

0 PLACES ±

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

THIRD ANGLE PROJECTION

CURRENT REV DESC:

EC NO: 719890
DRWN: NARENC
CHK'D: SMARUYAMA
APPR: YNAITO

INITIAL REVISION:
DRWN: MNABEI
APPR: NUKITA

2022/08/24
2022/09/05
2022/09/05

2008/06/27
2008/06/30

0.5 FPC CONN ZIF SMT RA
-LEAD FREE-

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER

DOC TYPE

DOC PART

REVISION

SD-52746-029

PSD

003

E

MATERIAL NUMBER

CUSTOMER

SHEET NUMBER

SEE TABLE

GENERAL MARKET

2 OF 2

52746-**70

MODEL NO.

DOCUMENT STATUS	P1	RELEASE DATE	2022/09/05	05:51:56
-----------------	----	--------------	------------	----------