

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: Chassis mount jack for 5.5x2.5mm female barrel connector. Unique 50VDC/8A rating, solder tabs Model No. High Power DC Connectors Part No./Ordering No. JACK-L-PANEL-8A(R) Rev B2
---	--

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification

ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <http://www.globtek.com/iso-certificates/>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<http://www.globtek.com/terms-and-conditions/>).

Prop 65 Statement:<https://www.globtek.com/prop-65-statement.pdf>

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.

A delay in receipt of this form will delay delivery schedule.

Company Name:

Customer P/N:

Quote Number:

Date:

Authorized Representative Name:

Authorized Representative Signature:

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: Chassis mount jack for 5.5x2.5mm female barrel connector. Unique 50VDC/8A rating, solder tabs		
	Model No. High Power DC Connectors		
	Part No./Ordering No. JACK-L-PANEL-8A(R)	Rev B2	

REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
B2	Update the datasheet to add "Similar to: " and "Mates with:"	QA	01/24/2024	QA
B1	Update operating temperature: -20°C to +70°C	QA	11/03/2022	QA
B	Add the panel cut out drawing to the spec, add Operating temperature -25°C to 85°C	QA	05/04/2022	QA
A1	Update to SF format, add tab material and plating	QA	11/03/2021	QA
A	Initial release	QA	08/16/2018	QA

3D CAD FILE:

[https://en.globtek.com/pdf/JACK-L-PANEL-8A\(R\).stp](https://en.globtek.com/pdf/JACK-L-PANEL-8A(R).stp)

AGENCY ONLINE DOCUMENTS





RoHS/RoHS3 Declaration <https://www.globtek.com/dcs/SPJ8VNR/n4cgF8ddvVFtn9QtDAf2vA>

REACH Declaration <https://www.globtek.com/r2/eM2co8>

Conflict Minerals Declaration <https://www.globtek.com/r2/SNw6P3>

Prop 65 Statement <https://www.globtek.com/r2/VMPRnr>

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.



Mounting Hole



	MATERIAL	PLATING
Center pin	copper	nickel
Metal case	copper	nickel
Outer spring contact	copper	nickel
Plastic	PPA	
Pins	copper	Bright tin (optional matte tin)

SPECIFICATIONS					
parameter	conditions/description	min	typ	max	units
rated input voltage			50		Vac
rated input current				8	A
contact resistance				30	mΩ
insulation resistance		100			MΩ
voltage withstand	at 50/60Hz for 1 minute	1500			Vac
Relative humidity				95% (40°C)	
life		10000			cycles

1. Operating temperature -20°C to +70°C
2. Similar to: 712AFMS 54-00064 57-PJ20
- Mates with: T-L-95-S(R) T-L-12-S(R) T-L-14-S(R) 760 765 KLDX-PA-0202-B PP3-002B 55-00050
- EP501B 4840.1210

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: Chassis mount jack for 5.5x2.5mm female barrel connector. Unique 50VDC/8A rating, solder tabs	
	Model No. High Power DC Connectors	
	Part No./Ordering No. JACK-L-PANEL-8A(R)	Rev B2

PACKAGING

Packing Spec P/N:	
Box Qty:	1000
Gift Box Size (mm):	
Gift Box Color:	White
Master Carton Size (mm):	TBD
Master Carton Cubic Volume (m³): 0.00	
Master GW (Kg):	kg
wt Ea. (Kg):	kg
wt Ea. (Kg):	kg
LABEL SPECS: Standard GT,L-1186	
PACK SPEC:	