


May.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
<b>APPLICABLE STANDARD</b>									
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C			STORAGE TEMPERATURE RANGE	— °C TO — °C			
	VOLTAGE	AC 250 V			OPERATING HUMIDITY RANGE	— % TO — %			
	CURRENT	0.5 A			APPLICABLE CABLE	UL20276 AWG NO.28 (φ 0.58)			
<b>SPECIFICATIONS</b>									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
<b>CONSTRUCTION</b>									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			○	○
MARKING		CONFIRMED VISUALLY.						○	○
<b>ELECTRIC CHARACTERISTICS</b>									
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).			35 mΩ MAX. <span style="border: 1px solid black; padding: 0 2px;">1</span>			○	○
INSULATION RESISTANCE		500V DC.			500 MΩ MIN.			○	○
VOLTAGE PROOF		500 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			○	○
<b>MECHANICAL CHARACTERISTICS</b>									
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE } 38.2 N MAX. EXTRACTION FARCE } 10.2 N MIN.		○	—	
MECHANICAL OPERATION		1000 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: <span style="border: 1px solid black; padding: 0 2px;">1</span> 35mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		○	—	
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, - m/s <sup>2</sup> AT 2 h, FOR 3 DIRECTIONS.			NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		○	—	
SHOCK		490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 6 DIRECTION.					○	—	
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 5~35 → 85 → 5~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 5 CYCLES.			NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	—
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 °C, 90~95 %RH, 96 h.			① INSULATION RESISTANCE AT HIGH HUMIDITY 1 MΩ MIN. AT DRY 100 MΩ MIN. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		○	—	
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			NO HEAVY CORROSION.			○	—
NOTE <span style="border: 1px solid black; padding: 0 2px;">1</span> CONTACT RESISTANCE TEST POSITION.									
									
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
Unless otherwise specified, refer to JIS C 5402.					<i>F. Sanjugh</i>	<i>L. Wada</i>	<i>Y. Enani</i>	<i>H. Miura</i>	
					02.04.05	02.04.05	02.4.5	02.04.09	
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test									
<b>HRS</b> HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET			PART NO. DX40M-26P		
CODE NO.(OLD) CL		DRAWING NO. ELC4-045315			PART NO. CL230-5034-8			1/1	