

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

5023821370

Status:

Active

Overview:

CLIK-Mate Wire-to-Board Connectors

Description:

1.25mm Pitch CLIK-Mate Wire-to-Board PCB Receptacle, Single Row, Vertical, Tin Plating, 13 Circuits



Series image - Reference only

Documents:

[3D Model \(PDF\)](#)

[Drawing \(PDF\)](#)

[3D Model](#)

[Product Specification PS-502382-001-001 \(PDF\)](#)

[Application Specification AS-502380-002-001 \(PDF\)](#)

[Packaging Specification SPK-502382-001-001 \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification		
UL		E29179
General		
Product Family		PCB Receptacles
Series		502382
Application		Signal, Wire-to-Board
Component Type		PCB Receptacle
Overview		CLIK-Mate Wire-to-Board Connectors
Product Name		CLIK-Mate
Taxonomy		PCB Headers and Receptacles
UPC		822350895309
Physical		
Circuits (Loaded)		13
Circuits (maximum)		13
Color - Resin		Natural
Durability (mating cycles max)		30
Glow-Wire Capable		No
Guide to Mating Part		Yes
Keying to Mating Part		Yes
Lock to Mating Part		Yes
Mated Height		7.80mm
Material - Metal		Copper Alloy
Material - Plating Mating		Tin
Material - Plating Termination		Tin
Material - Resin		High Temperature Thermoplastic
Net Weight		562.801/mg
Number of Rows		1
Orientation		Vertical
PCB Locator		No
PCB Retention		Yes
Packaging Type		Embossed Tape on Reel
Pitch - Mating Interface		1.25mm
Pitch - Termination Interface		1.25mm
Plating min - Mating		1.016µm
Plating min - Termination		1.016µm
Polarized to Mating Part		Yes
Polarized to PCB		No
Stackable		No
Temperature Range - Operating		-40° to +105°C
Termination Interface: Style		Surface Mount
Electrical		
Current - Maximum per Contact		1.0A

EU ELV	
Not Relevant	
EU RoHS	China RoHS
Compliant	
REACH SVHC	
Not Contained Per - D(2022)4187-DC (10 June 2022)	
Halogen-Free	
Status	
Not Low-Halogen	
For more information, please visit Contact US	
China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

502382 Series

Mates With

502380 CLIK-Mate Housing

Voltage - Maximum	50V AC (RMS)/DC
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-502380-002-001
Packaging Specification	SPK-502382-001-001
Product Specification	PS-502382-001-001
Sales Drawing	SD-502382-002-001, SD-502382-002-002, SD-502382-002-003, SD-502382-003-001

This document was generated on 01/04/2023

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION