




Power Double Lock

TE Internal #: 179593-2
Receptacle Contact, Tin, 300 VAC / 50 VAC, Locking Lance Contact Retention, 20 – 16 AWG Wire Size, .52 – 1.38 mm² Wire Size, Crimp, Power Double Lock

[View on TE.com >](#)

Connectors > Contacts > Connector Contacts



Contact Type: **Receptacle**
Contact Mating Area Plating Material: **Tin**
Wire Contact Termination Area Plating Material: **Pre-Tin**
Operating Voltage: **50 VAC, 300 VAC**
Contact Retention Within Housing: **With**

Features

Product Type Features

Discrete Wire Type	Stranded
--------------------	----------

Packaging Features

Packaging Quantity	1000
Packaging Method	Bag

Dimensions

Compatible Insulation Diameter Range	1.8 – 3.1 mm[.071 – .12 in]
Wire Size	.52 – 1.38 mm²

Mechanical Attachment

Wire Insulation Support	With
Contact Retention Type Within Housing	Locking Lance

Contact Features

Contact Orientation	Straight
Contact Mating Area Plating Material Thickness	.8 µm[31.49 µin]



Mating Tab Width	1.5 mm[.06 in]
Mating Tab Thickness	.5 mm[.02 in]
Wire Contact Termination Area Plating Thickness	.8 µm[31.49 µin]
Contact Type	Receptacle
Contact Mating Area Plating Material	Tin
Wire Contact Termination Area Plating Material	Pre-Tin
Contact Retention Within Housing	With
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	14 A

Electrical Characteristics

Operating Voltage	50 VAC, 300 VAC
-------------------	-----------------

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Other

EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-P87024-P729
STD Temp Power Double Lock Plug

TE Part # 917354-1
AMP POWER D/LOCK PLUG HDR 12P

TE Part # 234912-1
EXT TOOL FOR POWER DBL LOK REC

TE Part # 91569-1
CCII POWER DBL LOCK L REC TAB 20-16 ASSY

Also in the Series | Power Double Lock

Connector Contacts(24)

Connector Hardware(14)




Insertion & Extraction Tools(2)

PCB Headers & Receptacles(43)

Rectangular Power Connectors(240)

Customers Also Bought



 TE Part #1-440129-2 2.0MM,HSG,12POS	 TE Part #177901-1 STD Temp Power Double Lock Plug	 TE Part #53440-1 ELECTRO-TAP, 18-14 AWG RUN&TAP	 TE Part #1-353293-5 1.5 MINI-CT RECEPTACLE
 TE Part #353293-3 MINI CT MT REC ASSY 3P GRAY	 TE Part #928343-8 STD-TIMER GEH 8P	 TE Part #927766-3 JPT REC 2.8 Contact SWS Sn	TE Part #690501-4 CAM, TERMINAL FEED

Documents

Product Drawings

POWER D/LOCK REC CONT. H/P L/P

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_179593-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_179593-2_C.3d_stp.zip

English

Customer View Model

ENG_CVM_179593-2_C.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_179593-2_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_179593-2_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_179593-2_O.3d_stp.zip

English



By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages
SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English
1773458-5_POWER_DBL_LOCK_(PDL)_CONNECTORS

English

Product Specifications
Application Specification

English

Instruction Sheets
Instruction Sheet (non U.S.)

Japanese

Agency Approvals
UL Report

English