ADELS contact

## Screw Terminal Blocks

# 2000/12 DS



terminal block, 12 pole, cross-section rating: 16.0 mm², pin spacing: 14.50 mm, mounting hole diameter: 4.3 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 76 A

## Order Info

| | |
|---|---|
| **reference number (ref.no.)** | 128312 |
| **PU** | 20 |
| **EAN** | 4028012106585 |

## Type

| | |
|---|---|
| **type** | terminal block |
| **number of poles** | 12 pole |
| **clamping units per pole** | 1 |
| **colour** | natural |
| **cross-section rating** | 16.0 mm² |
| **wire protector (DS)** | yes |

## Technical Data

| | |
|---|---|
| **voltage rating** | 500 V |
| **current rating** | 76 A |
| **contact material** | brass |
| **core cross-section min.** | 0.5 mm² |
| **core cross-section max.** | 10.0 mm² |
| **flammabilty rating** | V-2 |
| **min. ambient temperature** | -40 °C |
| **max. ambient temperature operation** | 85 °C |
| **type of conductor solid** | yes |
| **type of conductor flexible** | yes |
| **type of conductor stranded** | yes |
| **stripping length** | 10.0-10.5 mm |
| **assembly contact screw** | 1,0x5,5 / ↻ 2,0 Nm |
| **mounting hole diameter** | 4.3 mm |
| **pin spacing** | 14.50 mm |
| **fixing** | screw |

## Approvals

| | |
|---|---|
| **acc. to EN 60998** | Download PDF |
| **acc. to UL** | Download PDF |
| **acc. to CSA** | Download PDF |

## Accessories

| | |
|---|---|
| **ZEL 110** | 196420 |