

4

3

2

I

© 2023 TE Connectivity. All Rights Reserved.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

SMART PART NUMBER

2MM - HB - D ____ - VS - 00 - ____ - ____

PRODUCT SERIES

2MM

AMPMODU 2mm series

GENDER / TYPE

HB

Breakaway headers

NUMBER OF ROWS

D

Double row

NUMBER OF PINS PER ROW

XX

02 through 25
(enter two digits)

ORIENTATION & TERMINATION

VS

Vertical surface mount

PACKAGING

TBP

Tube with cap

TRP

Tape and reel with cap

PLATING

T

Tin

F

0.1µm selective Gold (Gold flash)

M

0.38µm selective Gold

H

0.76µm selective Gold

TAIL LENGTH

00

N/A for surface mount

8

SMART PN EXAMPLES :

1. AMPMODU 2MM, BREAKAWAY HEADER, DOUBLE ROW , 04 POSITION PER ROW , SURFACE MOUNT, TAIL LENGTH NOT APPLICABLE, TIN PLATING, TUBE WITH CAP
2MM-HB-D04-VS-00-T-TBP

2. AMPMODU 2MM, BREAKAWAY HEADER, DOUBLE ROW , 25 POSITION PER ROW , SURFACE MOUNT, TAIL LENGTH NOT APPLICABLE, 0.76µm SELECTIVE GOLD PLATING, TAPE AND REEL WITH CAP
2MM-HB-D25-VS-00-H-TRP

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±0.1
2 PLC ±0.05
3 PLC ±
4 PLC ±
ANGLES ±°
FINISH

MATERIAL

SEE NOTES

DWN 11FEB2016
CHK 14APR2016
APVD 14APR2016
PRODUCT SPEC
APPLICATION SPEC
WEIGHT

108-64040
114-64040

CUSTOMER DRAWING

TE

TE Connectivity

NAME

AMPMODU 2mm, BREAKAWAY HEADER
DUAL ROW , VERTICAL,SMD

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A2

00779

©=2823142

-

SCALE

1:1

SHEET

2

OF

3

REV

A2

1471-9 (3/13)

