






P	LTR	DESCRIPTION	DATE	DWN	APVD
	NC	NEW RELEASE PER E.O. PI6753	21JULY2000	-	RDR
	B	REVISED PER PCN-24-226269	10JAN2025	AJT	MB




4. MATERIAL: CONNECTOR: PA66 GF15, GRAY
CAP: PA66 GF15, BLACK
WEDGE LOCK (INCLUDED): PBT GF30 (GREEN)
PINS: COPPER ALLOY, NICKEL PLATED

3. THE 6 PIN BUSBAR HAS A MAXIMUM CURRENT RATING OF 39 AMPS.

2. ORIENTATION OF "DEUTSCH" AND "-P021" TO BE OPTIONAL.

1. MATES WITH DT06-6S-XXXX (XXXX = ALL MODIFICATIONS).
CONSULT FACTORY FOR MODIFICATIONS.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T. YOHANNES 06 JULY 2000	 TE Connectivity		
DIMENSIONS: INCHES[mm]		CHK - 11 JULY 2000			
		APVD - 21 JULY 2000	NAME DT 6 WAY RECEPTACLE 6 PIN BUSBAR NICKEL PLATED COLOR: GRAY		
		PRODUCT SPEC 108-151009			
MATERIAL 4		APPLICATION SPEC 114-1510009	SIZE A3		
		WEIGHT 14 g			
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ±025[0,63] 4 PLC ± ANGLES ± FINISH -		CUSTOMER DRAWING	SCALE 2:1	SHEET 1 OF 1	RESTRICTED TO - REV B