



Positive Lock | Positive Lock 187

TE Internal #: 172074-2

Receptacle, Receptacle, 1 Position, Straight, UL 94V-2, Black, Nylon,
Contact Mating Retention, Positive Lock 187, Crimp Terminal
Housings

[View on TE.com >](#)

Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **1**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-2**

Features

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With

Product Type Features

Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Wire & Cable
Sealable	No
Connector System	Wire-to-Board, Wire-to-Wire

Configuration Features

Number of Positions	1
---------------------	---

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Body Features

--	--



Primary Product Color	Black
-----------------------	-------

Housing Features

Housing Material	Nylon
------------------	-------

Mechanical Attachment

Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Mating Alignment Type	Polarization

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Other

EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

Packaging Features

Packaging Quantity	1000
--------------------	------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts

TE Part # 724659-1 EXT TOOL FOR POSITIVE .187	TE Part # 170330-2 PL 187 RECEPTACLE 24-20 AWG NPPHBZ	TE Part # 170332-1 PL 187 RECEPTACLE 18-14 AWG PTPBR	TE Part # 170324-2 PL 187 RECEPTACLE 24-20 AWG 0.3 NPCU
TE Part # 170326-5 187 PL MKII REC. 18-14AWG PTPB	TE Part # 170326-1 187 PL MKII REC. 18-14AWG PTBR	TE Part # 170325-5 187 PL MKII REC. 20-16AWG PTBR	TE Part # 170325-1 187 PL MKII REC. 20-16AWG PTBR
TE Part # 170324-1 187 PL MKII REC. 24-20AWG PTBR	TE Part # 170331-1 PL MKII 187 REC 20-16AWG PTBR LP	TE Part # 170330-1 PL MKII 187 REC 24-20AWG PTBR LP	

Also in the Series | Positive Lock 187

Crimp Terminal Housings(86)	Insertion & Extraction Tools(2)	Insulation Boots & Sleeves(7)	Quick Disconnects(57)

Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_172074-2_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_172074-2_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_172074-2_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Positive Lock Receptacles

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English