


SCVF SERIES PART NUMBERING SCHEME

REV	ECN	APP'D
-	4502	IQ 5/30/01
A	4974	IQ 9/10/02
B	5742	RN 12/28/05



RATINGS

CURRENT - 12A
 VOLTAGE - 300V
 U.L. FILE NO. PENDING



RATINGS

CURRENT - 12 A
 VOLTAGE - 300 V
 CSA FILE NO. PENDING

DIN VDE 0627:1986
 DIN VDE 0110-1:1989
 EN 60947-1:1991
 EN 60947-7-1:1992

CURRENT - 12 A
 VOLTAGE - 300 V
 TUV FILE NO. PENDING

CONSULT PCD FOR PART NO. AND
 AVAILABILITY OF FOLLOWING OPTIONS:

- * CUSTOM COLORS
- * CUSTOM MARKING
- * CUSTOM KEYING
- * SELECTIVE CONTACT LOADING

INSTALLATION RECOMMENDATIONS:

WIRE RANGE: AWG #16-28, STRANDED OR SOLID
 WIRE STRIP LENGTH: .330" (8,38mm)

MATERIALS:


HOUSING: PA 66-6, UL 94 V-0
 CONTACT: COPPER ALLOY, TIN
 OR GOLD FINISH
 SPRING CLAMP: STAINLESS STEEL

MAX OPERATING TEMP: 105°C


DIMENSIONS ANSI Y14.5M UNITS: INCHES Pro/E FILE	TOLERANCES .XX ±0.15 .XXX ±0.006 ANGLES ±2.0°	PROJECTION 	Amphenol Pcd ENGR C. LASHUA5/29/01		TITLE SCVF SERIES FRONT/FRONT SPRING CLAMP TERMINAL BLOCK: .150 CL				
ORIGINAL STAMPED IN RED	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF AMPHENOL PCD, INC. PEABODY, MA, USA		CHKD I. QUINN5/30/01		SIZE A	DWG NO. SCVF02400		REV B	
			APPD I. QUINN5/30/01		CODE: 58982 SCALE: NONE SHEET 1 OF 2				

L=NUM OF POS X CL SPACING

SCVF WITHOUT EARS



SCVF WITH EARS



SIZE
A

DWG NO.

SCVF02400

REV
B

CODE: 58982

SCALE: NONE

SHEET 2 OF 2