

Applicable standard								
Rating	Operating temperature range	-35°C to + 85°C (Note 1)			Storage temperature range	-10°C to + 60°C (Note 3)		
	Operating humidity range	20 % to 80 % (Note 2)			Storage humidity range	40 % to 70 % (Note 3)		
	Voltage	AC/DC 100V			Applicable connector 	DF50A-*P-1V (##) DF50A-*P-1H (##)		
	Current 	Contact	2	3to16	Applicable Contact 	DF50-26SCFA (##) DF50-2830SCFA (##) DF50K-2830SCFA (##) DF50-3032SCFA (##)		
		AWG26	2. 0A	1. 0A				
AWG28		2. 0A	1. 0A					
AWG30		0. 9A						
AWG32	0. 7A							
Specifications								
Item		Test method			Requirements		QT AT	
Construction								
General examination		Visually and by measuring instrument.			According to drawing.		X X	
Marking		Confirmed visually.					X X	
Electric characteristics								
Insulation resistance		100V DC.			500MΩ MIN.		X —	
Voltage proof		300V AC for 1 min.			No flashover or breakdown.		X —	
Mechanical characteristics								
Mechanical operation		30times insertions and extractions.			No damage, crack or looseness of parts.		X —	
Vibration		Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for each, for 3 directions.					X —	
Shock		490 m/s ² duration of pulse 11 ms At 3 times for 3 directions.					X —	
Environmental characteristics								
Damp heat (Steady state)		Exposed at 40 ± 2 °C, 90 to 95 %, 96 h.			① Insulation resistance: 100MΩ MIN. ② No damage, crack or looseness of parts.		X —	
Rapid change of temperature		Temperature -55→+85°C Time 30→ 30min. Under 5 cycles. (The transferring time of the tank is 2 to 3 min)			① Insulation resistance: 500MΩ MIN. ② No damage, crack or looseness of parts.		X —	
Remarks								
Note 1: Include the temperature rising by current.								
Note 2: No condensing.								
Note 3: Apply to the condition of long term storage for unused products before harness assembly. After harness assembly, operating temperature and humidity range is applied for interim storage during transportation.								
	Count	Description of revisions		Designed		Checked	Date	
	3	DIS-H-00005434		HT. SATO		SZ. ONO	20191028	
Unless otherwise specifid , refer to IEC 60512.						Approved	KI. AKIYAMA	20100706
						Checked	OM. MIYAMOTO	20100706
						Designed	TT. OHSAKO	20100705201 00706
						Drawn	TT. OHSAKO	20100705
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				Drawing no.		ELC-332936-00-00		
	Specification sheet			Part no.		DF50A-*S-1C		
	Hirose electric co., ltd.			Code no.		CL665-	 1/1	