



Part Number : [314022510](#)
Product Description : 2.54mm MX64 Sealed
Single Row Crimp Housing, GET Terminal,
Black, 2 Circuits, Key B, with CPA Lock
Series Number : 31402
Status : Active
Product Category : Connector Housings
Engineering Number : CVP-314022510



Documents & Resources

Drawings
[314022510_sd.pdf](#)
[PK-31300-256-001.pdf](#)

3D Models and Design Files
[314022510_stp.zip](#)

Specifications
[314020000-000.pdf](#)
[AS-31402-000-001.pdf](#)
[PS-31402-000-001.pdf](#)
[TS-31402-001-1X2-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant
China RoHS	Not Relevant
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Relevant
REACH SVHC	Contains Dodecamethylcyclohexasiloxane; Decamethylcyclopentasiloxane; Octamethylcyclotetrasiloxane per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	31402
Description	2.54mm MX64 Sealed Single Row Crimp Housing, GET Terminal, Black, 2 Circuits, Key B, with CPA Lock
Application	Power, Wire-to-Board
Product Name	MX64
UPC	887191055787

Physical

Circuits (maximum)	2
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	PBT
Net Weight	4.710/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No

Pitch - Mating Interface	2.54mm
Polarization	B
Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +125°C

Mates With / Use With

Mates with Part(s)

Description	Part Number
Mates With	Sensors, Other USCAR Interfaces