

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0919991999](#)
Status: **Active**
Overview: RAST Connector System
Description: Appli-Mate RAST 5 Header, Vertical, 4 Circuits, Silver (Ag) Plating, Glow-Wire Capable

Documents:

Drawing (PDF)	Product Specification PS-99020-0037-001 (PDF)
3D Model	Packaging Specification PK-90858-001-001 (PDF)
3D Model (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179

Application tooling part link

Application Tooling Part Link	216658-0200
-------------------------------	-------------


General

Product Family	PCB Headers
Series	91999
Application	Power, Wire-to-Board
Comments	This Molex product is manufactured from material that has the following ratings, tested by independent agencies: a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12 and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options.

Component Type	PCB Header
Overview	RAST Connector System
Product Name	RAST 5
Taxonomy	PCB Headers and Receptacles
UPC	883906120559

Physical

Breakaway	No
Circuits (Loaded)	4
Circuits (maximum)	4
Color - Resin	Natural
Durability (mating cycles max)	10
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	Yes
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - D(2022)4187-DC (10 June 2022)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[91999 Series](#)

Mates With

Appli-Mate RAST 5 IDT Housing [91778](#) , [91779](#)

Use With

RAST Standard Interface

Application Tooling | [FAQ](#)

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

RAST 5 Power

[2166580200](#)

Semi-Automatic IDC Machine

Material - Metal	Brass
Material - Plating Mating	Silver
Material - Plating Termination	Nickel
Material - Resin	Nylon
Net Weight	4.334/g
Number of Rows	1
Orientation	Vertical
PC Tail Length	3.90mm
PCB Locator	Yes
PCB Retention	None
PCB Thickness - Recommended	1.40mm
Packaging Type	Bag
Pitch - Mating Interface	5.00mm
Pitch - Termination Interface	5.00mm
Plating min - Mating	2.032µm
Polarized to PCB	Yes
Shrouded	Fully
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-20° to +120°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	16.0A
Voltage - Maximum	250V AC

Material Info

Engineering Number	WITH ZYTEL RM
--------------------	---------------

Reference - Drawing Numbers

Packaging Specification	PK-90858-001-001
Product Specification	PS-99020-0037-001
Sales Drawing	919990001-000

This document was generated on 01/04/2023

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION