
ADELS contact

Screw Terminal Blocks

230/12 DS



terminal block, 12 pole, cross-section rating: 2.5 mm², pin spacing: 8.00 mm, mounting hole diameter: 2.8 mm, wire protector (DS): yes, fixing: screw, voltage rating: 450 V, current rating: 24 A

Order Info

reference number (ref.no.)	121312
PU	50
EAN	4028012105274

Type

type	terminal block
number of poles	12 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm²
wire protector (DS)	yes

Technical Data

voltage rating	450 V
current rating	24 A
contact material	brass
core cross-section min.	0.5 mm²
core cross-section max.	2.5 mm²
flammabilty rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	5.0-5.5 mm
assembly contact screw	0,8x4,0 / ↻ 0,5 Nm
mounting hole diameter	2.8 mm
pin spacing	8.00 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

230 BZ/12	191212
ZEL 110	196420