



Part Number : [2080353044](#)
Product Description : ConnTAK50 Header,
Single Row, Vertical, Surface Mount, 4 Circuits,
Key D, Violet, with Pick-and-Place Tape
Series Number : 208035
Status : Active
Product Category : PCB Headers and
Receptacles



Documents & Resources

Drawings
[2080353044_sd.pdf](#)

3D Models and Design Files
[2080353044_stp.zip](#)

Specifications
[2046310000-AS-000.pdf](#)
[2046310000-PS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Reviewed
China RoHS	Not Relevant
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Relevant
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements
- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents
- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	208035
Description	ConnTAK50 Header, Single Row, Vertical, Surface Mount, 4 Circuits, Key D, Violet, with Pick-and-Place Tape
Application	Automotive, Power, Signal, Wire-to-Board
Component Type	PCB Header
Product Name	ConnTAK50
UPC	193264050062

Electrical

Current - Maximum per Contact	3.0A (for reference only), See Product Specification
Voltage - Maximum	14V AC/DC

Physical

Breakaway	No
Circuits (Loaded)	4
Circuits (maximum)	4
Color - Resin	Violet
Durability (mating cycles max)	10
First Mate / Last Break	No
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Brass

Material - Plating Mating	Matte Tin
Material - Resin	High Temperature Nylon
Net Weight	1.100/g
Number of Rows	1
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Retention	None
Pitch - Mating Interface	1.80mm
Pitch - Termination Interface	1.80mm
Plating min - Mating	1.000µm
Polarized to Mating Part	Polarizing Ribs
Polarized to PCB	No
Robotic Placement	Vacuum Pick-Up Tape
Shrouded	Fully
Temperature Range - Operating	-40° to +100°C USCAR Class T2, -40° to +105°C LV-214
Termination Interface Style	Surface Mount

Mates With / Use With

Mates with Part(s)

Description	Part Number
ConnTAK50 Single Row Tang Receptacles	<u>205827</u>