




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.31 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Dimensions

Wire Size	.51 – 1.31 mm²
Product Length	16.9 mm[.665 in]
Compatible Insulation Diameter Range	2.01 – 3 mm[.079 – .118 in]
Terminal Material Thickness	.51 mm[.02 in]

Packaging Features

Packaging Method	Loose Piece/Carton
------------------	--------------------



Packaging Quantity	1000
Product Type Features	
Insertion Force	Normal
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
Other	
EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single
Termination Features	
Product Terminates To	Wire & Cable
Mechanical Attachment	
Locking Lance Height	.89 mm
Wire Insulation Support	With
Mating Retention Type	Locking Lance
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2150034-1
OCEAN_2.0_APPLICATOR-E-110F180F-REM

KIT
TE Part # 7-2150034-7
OCEAN_2.0_SPARE_PART_KIT-110F180F

TE Part # 2150034-2
OCEAN_2.0_APPLICATOR-E-110F180FA-REA

TE Part # 968864-2
2 POS. FASTON HOUSING

Also in the Series | FASTIN-FASTON 110

Automotive Housings(6)

Automotive Terminals(5)

Crimp Terminal Housings(34)

Insertion & Extraction Tools(3)

Quick Disconnects(83)

Customers Also Bought



TE Part #6609053-9
10EHT1=F7667 S0




TE Part #1-1564526-1
18POS,TAB 1.6X0.6,TAB HSG,ASSY



TE Part #963531-1
BLINDSTOPFEN



TE Part #T4061120004-001
M8 CABLE ST M 0.5M 4POS PUR CABLE




TE Part #776299-2
ASSEMBLY SOCKET LOOSE PC NICKE



TE Part #1564411-2
SLIDE,TAB HSG GROUP E



TE Part #963904-1
TIMER, RECEPTACLE AND TAB



TE Part #106462-1
2P.FASTIN-ON HSG.

Documents

Product Drawings
FF 110 REC 20-16AWG BR

English

CAD Files
3D PDF

3D

Customer View Model
ENG_CVM_CVM_170042-1_F.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_170042-1_F.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_170042-1_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications
Product Specification

English