





A

B

C

D



PERFORMANCE CHARACTERISTICS :

CURRENT RATING : 1.5A AT 20°C (FULLY LOADED)
1A AT 70°C (FULLY LOADED)
RATED VOLTAGE : 500V AC (CONT / CONT)
OPERATING TEMPERATURE : -55°C TO 125°C
CONTACT RESISTANCE : 25mΩ MAX.
INSERTION FORCE : 0.75 N MAX / CONT
EXTRACTION FORCE : 0.15 N MIN / CONT
INSULATION RESISTANCE : 10⁴ MΩ MIN.

NOTES :

- UL APPROVED WITH USR AND CNR.
- MEASURED AT THE BOTTOM.
- MATERIAL CONTACT : PHOSPHORBRONZE.
HOUSING : LCP 30% GLASS-FILLED.
- CONNECTOR PRINTED WITH P/N AND DATE CODES.
- FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.}
- 4 = LEVEL 1 (5.30)
5 = LEVEL 2 (6.80)
6 = LEVEL 3 (8.30)
- HM2J71PE5118-
LEAD FREE INDICATOR : LF = LEAD FREE
PERFORMANCE LEVEL INDICATOR
(Ref DWG No BS,C ,201844,003)
- FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS,A ,201572,001
- THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-0004

LOADING PATTERN : MATING SIDE

F	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	
E	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
D	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
C	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
B	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
A	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
Z	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19

spec ref	-	dr	P-Mathew Nebu	2011/05/25	projection	mm	size	A3	scale	1/1
tolerance std	ISO 406 ISO 1101	eng	Alex Babu	2019/11/11	chr	-	ecn no	ELX-I-26926-1	rel level	Released
surface	linear	appr	Kuriakose, San	2019/11/12	product family	MILLIPACS	cat. no.	HM2J71PE5118----	Product - Customer Drw	sheet 1 of 1
ISO 1302	angular	0°	±1°	Amphenol FCI	type B (19POS), shielded	dwg no	BSC202767020	rev	H	