

Jun.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD			
RATING	OPERATING TEMPERATURE RANGE	— °C TO — °C	STORAGE TEMPERATURE RANGE
	VOLTAGE	AC 250 V	OPERATING HUMIDITY RANGE
	CURRENT	3 A	APPLICABLE CABLE

SPECIFICATIONS

JACKET DIAMETER
1.5 TO 1.9 mm

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION	GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	○	○
	MARKING	CONFIRMED VISUALLY.		○	○

ELECTRICAL CHARACTERISTICS					
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	15 mΩ MAX.		○	—
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX. mA (DC OR 1000 Hz).	mΩ MAX.		—	—
INSULATION RESISTANCE	V DC	MΩ MIN.		—	—
VOLTAGE PROOF	V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN.		—	—

MECHANICAL CHARACTERISTICS					
CONTACT INSERTION AND EXTRACTION FORCES	□ 0.635 ± 0.002 BY STEEL GAUGE.	INSERTION FORCE 4.4 N MAX. EXTRACTION FORCE 0.56 N MIN.		○	—
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.		—	—
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS	① CONTACT RESISTANCE: 15 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		○	—
VIBRATION	FREQUENCY TO Hz, SINGLE AMPLITUDE mm, m/s ² AT h FOR DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF μs. ② CONTACT RESISTANCE: mΩ MAX.		—	—
SHOCK	m/s ² DURATION OF PULSE ms AT TIMES FOR DIRECTION.	① NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—	—

ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT °C, % h.	① CONTACT RESISTANCE: mΩ MAX. ② INSULATION RESISTANCE: MΩ MIN.		—	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE °C TIME min UNDER CYCLES.	① NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—	—
DAMP HEAT, CYCLIC	EXPOSED AT °C TO °C, % TOTAL TO h, CYCLES (h).	① CONTACT RESISTANCE: mΩ MAX. ② INSULATION RESISTANCE: MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—	—
DRY HEAT	EXPOSED AT °C, h.	① CONTACT RESISTANCE: mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		—	—
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 15 mΩ MAX. ② NO HEAVY CORROSION.		○	—
HYDROGEN SULPHIDE	EXPOSED IN PPM FOR h. (TEST STANDARD: JEIDA-38)			—	—
SULPHUR DIOXIDE	EXPOSED IN PPM FOR h. (TEST STANDARD: JEIDA-39)			—	—
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, °C FOR IMMERSION, s.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.		—	—
SOLDRABILITY	SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMersed.		—	—

REMARKS	CLIMP STRENGTH: 88.2 N Min. (AWG20)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	Unless otherwise specified, refer to MIL-STD-1344.	H. Sakamoto	H. Sakamoto	M. Matsuzawa	Y. Yoshimura	
		95.2.20	95.2.20	95.2.22	95.2.22	

Note QT: Qualification Test AT: Assurance Test ○: Applicable Test

HRS HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.
		HIF3-2022SCF
CODE NO. (OLD)	DRAWING NO.	CODE NO.
CL	ELC4-016947	CL 562-0493-7

TO
PCK