






ナイロン66, 94V-0
NYLON66,94V-0
色: オフホワイト
COLOR:OFF WHITE

注)
NOTE.

1. フリクションロック構成:
FRICTION LOCK CONFIGURATION:
4極までは1箇所
4CKT AND UNDER - 1LOCK
5極以上は2箇所
5CKT AND OVER - 2LOCKS

2. 嵌合相手: 5102-N
MATES WITH HOUSING:5102-N

3. スリット構成:
SLIT CONFIGURATION:
4極以下はなし
4CKT AND UNDER - NO SLIT
5及び6極は1箇所
5 AND 6CKTS - 1 SLIT
7極以上は2箇所
7CKT AND OVER - 2 SLITS

29-11-0143	5240-141	32.5	36.2	38.6	5	35.8	14
↑ -0123	↑ -121	27.5	31.2	33.6	5	30.8	12
↑ -0103	↑ -101	22.5	26.2	28.6	5	25.8	10
↑ -0093	↑ -091	20	23.7	26.1	5	23.3	9
↑ -0083	↑ -081	17.5	21.2	23.6	5	20.8	8
↑ -0073	↑ -071	15	18.7	21.1	5	18.3	7
↑ -0063	↑ -061	12.5	16.2	18.6	5	15.8	6
↑ -0053	↑ -051	10	13.7	16.1	3.75	13.3	5
↑ -0043	↑ -041	7.5	11.2	13.6	7.5	10.8	4
↓ -0033	↓ -031	5	8.7	11.1	5	8.3	3
29-11-0023	5240-021	2.5	6.2	8.6	2.5	5.8	2
EDP.NO.	ENG.NO.	B	C	(A)	(E)	(D)	極数 CKT.

GENERAL TOLERANCES (UNLESS SPECIFIED)				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													
DIMENSION		UNITS		SCALE		CURRENT REV DESC: REMOVED OBSOLETE PART NUMBERS AS PER PCN#514486.						molex MINI. SPOX PLUG HSG PRODUCT CUSTOMER DRAWING DOCUMENT NUMBER SD-5240-N1 DRAWING SEE CHART SERIES 5240 DRAWING A3-SIZE					
mm		2:1		GENERAL TOLERANCES (UNLESS SPECIFIED)													
ANGULAR TOL				± °		EC NO: 774109											
4 PLACES				±		DRWN: RAVINR12023/12/27											
3 PLACES				±		CHK'D: GGA2024/01/29											
2 PLACES				±		APPR: GGA2024/01/29											
1 PLACE				±		INITIAL REVISION:											
0 PLACES				±		DRWN: KKOHAMA2000/03/27											
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		APPR: TKANEKO2016/02/26											
																	