


Number of Contacts	Dimensions		
	A	B	F
2	2.54	5.08	5.00
3	5.08	7.62	
4	7.62	10.16	
5	10.16	12.70	
6	12.70	15.24	
7	15.24	17.78	
8	17.78	20.32	
9	20.32	22.86	
10	22.86	25.40	
11	25.40	27.94	
12	27.94	30.48	
13	30.48	33.02	
14	33.02	35.56	
15	35.56	38.10	
16	38.10	40.64	
17	40.64	43.18	
18	43.18	45.72	
19	45.72	48.26	
20	48.26	50.80	

Number of Contacts	Dimensions		
	A	B	F
21	50.80	53.34	
22	53.34	55.88	
23	55.88	58.42	
24	58.42	60.96	
25	60.96	63.50	
26	63.50	66.04	
27	66.04	68.58	
28	68.58	71.12	
29	71.12	73.66	
30	73.66	76.20	
31	76.20	78.74	
32	78.74	81.28	
33	81.28	83.82	
34	83.82	86.36	
35	86.36	88.90	
36	88.90	91.44	
37	91.44	93.98	
38	93.98	96.52	
39	96.52	99.06	
40	99.06	101.60	



No. of Contacts: 02 to 40

Contact Plating
A = Gold Flash All Over (Standard)
 B = Selective Gold Flash Contact Area/
 Tin On Tail
 C = Tin All Over
 G = 10µ" Gold Contact Area/Tin On Tail
 I = 30µ" Gold Contact Area/Tin On Tail

Type
 1 = R1 Type
 2 = R2 Type

Dimension C (1/100mm) (Post Height)
0400 = 4.00mm (Standard)
0450 = 4.50mm (Standard)
0650 = 6.50mm (Standard)
 Or specify Custom Post Height
 eg. 0250 = 2.50mm
 (Maximum 1500=15.00mm)
 (Minimum 0100=1.00mm)

Request Samples and Quotation

Packing Options
 B = Tape & Reel with Cap (Standard)
 D = Tube (D & E not available)
 E = Tube with Cap for 2-5 contacts.)
 G = Plastic Box

Insulator Material
 N = High Temperature Nylon (Standard)
 L = LCP

Dimension E (1/100mm) (PCB to Top of Insulator)
0350 = 3.50mm (Standard)
 Or specify custom dimension
 eg 0320 = 3.20mm (Minimum)

Dimension D (1/100mm) (Footprint Width)
0530 = 5.30mm (Standard)
 Or specify Custom Footprint Width
 eg. 0250 = 2.50mm
 (Tooling charge may apply)

Specifications

Material
 Contact: Copper Alloy
 Insulator:
 Standard: Polyamide, High Temperature Nylon, UL94V-0
 Option: Polymer, LCP, UL94V-0

Plating
 See Ordering Grid

Electrical
 Current Rating: 3 Amp Per Pin
 Contact Resistance: 20 mΩ max.
 Insulation Resistance: 1000 MΩ min.
 Dielectric Withstand Voltage: 600V AC

Mechanical & Environmental
 Operating Temperature:
 -40°C to +125°C (LCP)
 -40°C to +105°C (High Temperature Nylon)
Soldering Process
 (High Temperature Nylon & LCP)
 IR Reflow: 260°C for 10 sec.
 Manual Solder : 350°C for 3-5 sec.

Mates with (Subject to Pin Length)
 BG090 BG095 BG096 BG100 BG110
 BG115 BG125 BG126 BG130 BG135
 BG145 BG205 BG230

BG095 Recommended mating length 4.00mm
 BG115 Recommended mating length 4.00mm

Part Number		Product Description	
BG055		2.54mm Pitch Pin Header, Single Row, Surface Mount, Vertical	
Drawing Date		30th October 2006	
By	MW	Tolerances (Except as Noted)	Units: Metric (mm)
Detail	BG055	Length: X. ± 0.30	Angle: X° ± 5°
Revision	G5	G PCN: X.X ± 0.20	X.XX° ± 2°
Date	19/01/26	X.XX ± 0.15	X.XX° ± 1°
		X.XXX ± 0.10	X.XXX° ± 0.5°

Halogen Free

3rd Angle Projection

This drawing is confidential and copyright of Global Connector Technology, Ltd (GCT). This drawing must not be copied or disclosed without written consent. E & OE



www.gct.co

Not to Scale	Drawn By LYH	Sheet No. 1/1
--------------	--------------	---------------

H
G
F
E
D
C
B
A