

printed on 22 Aug 2022 11:56 (China Standard Time) from TE315078

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	E3	REVISED PER ECR-16-009984	22JUL2016	BW	EW
	F	REVISED PER ECR-22-124164	22AUG2022	M.G	D.Z

NOTES

1

MATERIAL: 66 NYLON (UL94 V-0)

2

SEE TABLE 1

3. INSTRUPTION SHEET: 411-5771.

4

PART 5-917688-1 COMPLY WITH GLOW WIRE REQUIREMENT FOR PARTS OF NON-METALLIC MATERIAL SUPPORTING A CURRENT-CARRYING CONNECTION DETAILED IN IEC 60335-1, SECTION 30(GWT)

TRADE MARK

2

CIRCUIT NO.

1

2

3

4

TABLE 1

TRADE MARK	MANUFACTURING PLACE
-AMP OR AMP	JAPAN
-+AMP OR AMP	CHINA

TE

TE Connectivity

2.5mm SIGNAL DBL-LOCK 4P PLUG HSG

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779

C-917688

-

CUSTOMER DRAWING

SCALE 4:1

SHEET 1 OF 1

REV F

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±

1 PLC ±0.25

2 PLC ±0.20

3 PLC ±

4 PLC ±

ANGLES ±3°

FINISH -

MATERIAL

-

DWN

Y. NOGUCHI

12MAY'95

CHK

Y. KASHIWA

12MAY'95

APVD

Y. KASHIWA

12MAY'95

PRODUCT SPEC

108-5459

APPLICATION SPEC

114-5203

WEIGHT

-

1470-19 (3/13)