

APPLICABLE STANDARD								
RATING	OPERATING TEMPERATURE RANGE	-45°C TO +125°C (NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO + 60°C (NOTE2)				
	VOLTAGE	150V AC	APPLICABLE CONNECTOR	DF9#—*P—1V (22)				
	CURRENT	0.5A		DF9#—*P—1V (32)				
SPECIFICATIONS								
ITEM		TEST METHOD		REQUIREMENTS				
CONSTRUCTION								
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.				
MARKING		CONFIRMED VISUALLY.						
ELECTRIC CHARACTERISTICS								
CONTACT RESISTANCE		100m A (DC OR 1000 Hz).		50mΩ MAX.	X —			
INSULATION RESISTANCE		100V DC.		500MΩ MIN.	X —			
VOLTAGE PROOF		250V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.	X —			
MECHANICAL CHARACTERISTICS								
MECHANICAL OPERATION		30TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 50mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
ENVIRONMENTAL CHARACTERISTICS								
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -65→ 5 TO 35→125→ 5 TO 35°C TIME 30→10 TO 15→ 30→10TO15min UNDER 5 CYCLES.		① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X —			
HEAT RESISTANCE OF SOLDERING		【RECOMMENDED TEMPERATURE PROFILE】 《SOLDERING AREA》 MAX250°C, 220°C FOR 60 SECONDS MAX. 《PREHEATING AREA》 150 TO 180°C 90~120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. 【RECOMMENDED MANUAL SOLDELING CONDITION】 SOLDERING IRON TEMPERATURE 380°C SOLDERING TIME : WITHIN 3 SECONDS.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X —			
SOLDERABILITY		SOLDERING TEMPARATURE:245±5°C DURATION OF IMMERSION : SOLDERING FOR 3SECONDS		A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95% OF THE SURFACE BEING IMMERSED.	X —			
△								
REMARKS								
NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT.								
NOTE2:STORAGEIS DEFINED AS LONG-TERM STORAGE OF UNUSED PRODUCTS.								
APPLY OPERATION TEMPERATURE RANGE TO PRODUCTS MOUNTED ON PCB WITHOUT POWER SUPPLY.								
UNLESS OTHERWISE SPECIFIED , REFER TO JIS C 5402 .								
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
△	1	DIS-H-001214	AR. TAKAHASHI	TS. MIYAZAKI	06.08.02			
			APPROVED	MO. NAKAMURA	05.10.31			
			CHECKED	TS. MIYAZAKI	05.10.31			
			DESIGNED	TY.001	05.10.31			
			DRAWN	HK. MURAKAMI	05.10.31			
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-162417-04			
SPECIFICATION SHEET			PART NO.	DF9A-*S-1V (22)				
HIROSE ELECTRIC CO., LTD.			CODE NO.	CL540	△ 1/1			