

| APPLICABLE STANDARD   |  |   |                           |                         |            |
|---|--|---|---------------------------|-------------------------|------------|
| RATING  | OPERATING TEMPERATURE RANGE  | -40 °C TO +85 °C(NOTE1)△2   | STORAGE TEMPERATURE RANGE | -10 °C TO +60 °C(NOTE2) |            |
|   | OPERATING TEMPERATURE RANGE  | 40 % TO 80 %  | STORAGE TEMPERATURE RANGE | 40 % TO 70 % (NOTE2)    |            |
|   | VOLTAGE  | 250 V AC  | CURRENT                   | 2A                      |            |
| SPECIFICATIONS  |  |   |                           |                         |            |
| ITEM  | TEST METHOD  | REQUIREMENTS  | QT                        | AT                      |            |
| CONSTRUCTION  |  |   |                           |                         |            |
| GENERAL EXAMINATION   | VISUALLY AND BY MEASURING INSTRUMENT.  | ACCORDING TO DRAWING.   | ×                         | ×                       |            |
| MARKING   | CONFIRMED VISUALLY.  |   | ×                         | ×                       |            |
| ELECTRIC CHARACTERISTICS  |  |   |                           |                         |            |
| CONTACT RESISTANCE  | 100 mA (DC OR 1000 Hz).  | 30 mΩ MAX.  | ×                         | —                       |            |
| INSULATION RESISTANCE   | 500 V DC.  | 1000 MΩ MIN.  | ×                         | —                       |            |
| VOLTAGE PROOF   | 650 V AC FOR 1 min.  | NO FLASHOVER OR BREAKDOWN.  | ×                         | —                       |            |
| MECHANICAL CHARACTERISTICS  |  |   |                           |                         |            |
| MECHANICAL OPERATION  | 50 TIMES INSERTIONS AND EXTRACTIONS.   | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.   | ×                         | —                       |            |
| VIBRATION   | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.   | ① NO ELECTRICAL DISCONTINUITY OF 1μs.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.                                    | ×                         | —                       |            |
| SHOCK   | 490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.  |   | ×                         | —                       |            |
| ENVIRONMENTAL CHARACTERISTICS   |  |   |                           |                         |            |
| DAMP HEAT (STEADY STATE)  | EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.  | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② INSULATION RESISTANCE: 500 MΩ MIN.<br>③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | ×                         | —                       |            |
| RAPID CHANGE OF TEMPERATURE   | TEMPERATURE -55 →5 TO 35→85 →5 TO 35 °C<br>TIME 30 →5 TO 15 →30 →5 TO 15 min<br>UNDER 5 CYCLES.  | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② INSULATION RESISTANCE: 1000MΩ MIN.<br>③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | ×                         | —                       |            |
| RESISTANCE TO SOLDERING HEAT  | 1)AUTOMATIC SOLDERING (FLOW)<br>SOLDER TEMPERATURE : 260±3°C FOR IMMERSION,DURATION : 10 sec.<br>2)MANUAL SOLDERING<br>SOLDERING IRON TEMPERATURE : 290±10°C<br>SOLDERING TIME : 2 sec.<br>NO STRENGTH ON CONTACT. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.   | ×                         | —                       |            |
| SOLDERABILITY   | SOLDERED AT SOLDER TEMPERATURE,240°C FOR IMMERSION DURATION,3 sec.   | SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMERSED   | ×                         | —                       |            |
| REMARKS   |  |   |                           |                         |            |
| NOTE1:INCLUDE THE TEMPERATURE RISING BY CURRENT.<br>NOTE2:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD,OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION. |  |   |                           |                         |            |
|   | COUNT  | DESCRIPTION OF REVISIONS  | DESIGNED                  | CHECKED                 | DATE       |
| △   | 1  | DIS-H-008540  | MI. SAKIMURA              | HK. UMEHARA             | 14. 02. 26 |
| Unless otherwise specified, refer to IEC 60512.   |  |   | APPROVED                  | TY. OMA                 | 06. 07. 26 |
|   |  |   | CHECKED                   | HK. UMEHARA             | 06. 07. 25 |
|   |  |   | DESIGNED                  | NS. HIROSE              | 06. 07. 25 |
|   |  |   | DRAWN                     | AK. MIURA               | 06. 07. 24 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test  |  |   | DRAWING NO.               | ELC4-162390-03          |            |
| <b>HRS</b>  | SPECIFICATION SHEET  |   | PART NO.                  | DF11-*DP-2DS (52)       |            |
|   | HIROSE ELECTRIC CO., LTD.  |   | CODE NO.                  | CL543                   | △ 1/1      |