

**MODEL:** UJC-HP-L-G-5-MSMT-TR | **DESCRIPTION:** USB RECEPTACLE**FEATURES**

- USB Type C receptacle
- designed for power only applications
- reflow solder compatible
- tape & reel packaging

**SPECIFICATIONS**


| parameter                       | conditions/description                     | min | typ   | max  | units  |
|---------------------------------|--------------------------------------------|-----|-------|------|--------|
| rated input voltage             |                                            |     |       | 20   | Vdc    |
| rated input current             | as per EIA-364-70, Method B                |     |       |      |        |
|                                 | power pins collectively [A9, A12, B9, B12] |     |       | 3.0  | A      |
|                                 | VCDNN pins individually [A5, B5]           |     |       | 1.25 | A      |
| contact resistance <sup>1</sup> | between terminals and mating plug          |     |       | 40   | mΩ     |
| insulation resistance           | between adjacent contacts                  | 100 |       |      | MΩ     |
| voltage withstand               | between adjacent contacts                  | 100 |       |      | Vac    |
| insertion force                 | at a rate of 12.5 mm/min                   | 5   |       | 20   | N      |
| withdrawal force                | at a rate of 12.5 mm/min                   | 8   |       | 20   | N      |
| life                            | at a rate of 200 cycles per hour           |     | 5,000 |      | cycles |
| operating temperature           |                                            | -30 |       | 85   | °C     |
| flammability rating             | UL94V-0                                    |     |       |      |        |
| RoHS                            | yes                                        |     |       |      |        |

Note: 1. When measured at 20 mV / 100 mA.  
2. All specifications measured at 10~35°C, humidity at 45~85%, under standard atmospheric pressure, unless otherwise noted.

**SOLDERABILITY**

| parameter                     | conditions/description      | min | typ | max | units |
|-------------------------------|-----------------------------|-----|-----|-----|-------|
| reel storage                  | at relative humidity 65~70% | 25  |     | 30  | °C    |
| reflow soldering <sup>3</sup> | see reflow profile          |     | 255 | 260 | °C    |


Note: 3. It is recommended to reflow solder within 3 months from opening vacuum packaging at a temperature of 25~30°C & relative humidity 65~70%.



MECHANICAL DRAWING

units: mm  
tolerance:  
X, ±0.50 mm  
X.X ±0.30 mm  
X.XX ±0.20 mm  
X.XXX ±0.10 mm  
unless otherwise noted

|           | MATERIAL        | PLATING                                                        |
|-----------|-----------------|----------------------------------------------------------------|
| insulator | LCP [UL94V-0]   | black                                                          |
| contact   | copper alloy    | contact area: gold flash<br>solder area: matte tin over nickel |
| shell     | stainless steel | nickel                                                         |




## MECHANICAL DRAWING (CONTINUED)

units: mm

PCB tolerance:  $\pm 0.05$  mm

PCB thickness: 0.8 mm

| PIN CONNECTIONS |                  |     |                  |
|-----------------|------------------|-----|------------------|
| PIN             | SIGNAL NAME      | PIN | SIGNAL NAME      |
| A5              | CC1              | B5  | CC2              |
| A9              | V <sub>BUS</sub> | B9  | V <sub>BUS</sub> |
| A12             | GND              | B12 | GND              |

Recommended PCB Layout  
Top View

## PACKAGING


units: mm

Reel Size:  $\varnothing 330$  mm

Reel QTY: 1,000 pcs per reel

Carton Size: 355 x 355 x 235 mm

Carton QTY: 10,000 pcs



REVISION HISTORY

| rev. | description                       | date       |
|------|-----------------------------------|------------|
| 1.0  | initial release                   | 06/16/2022 |
| 1.01 | logo, datasheet style update      | 08/05/2022 |
| 1.02 | CUI Devices rebranded to Same Sky | 09/12/2024 |

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**sameskydevices.com**