

D

C

B



A

D



C

B


A



LEAD FREE



- ⚠ MATERIAL:
SHELL & CONTACTS- COPPER ALLOY.
HOUSING- UL 94V-0 RATED, THERMOPLASTIC, SEE TABLE.
- ⚠ PLATING:
CONTACTS- 0.076 MICROMETERS MINIMUM GOLD OVER 0.76 MICROMETERS MINIMUM PALLADIUM-NICKEL ON MATING AREA. OR CONTACT ALTRENATE PLATING 0.76 MICROMETERS MINIMUM GOLD ON MATING AREA.
3.80 MICROMETERS MINIMUM TIN ON SOLDER TAILS.
BOTH OVER 1.27 MICROMETERS MINIMUM NICKEL.
SHELL: 2~5μm THICK TIN
- ⚠ DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- ⚠ RECOMMENDED PC BOARD THICKNESS OF 1.57.



YES	2.29±0.25	BLACK	5787745-5
YES	2.84±0.25	BLACK	5787745-4
NO	2.84±0.25	NATURAL	5787745-3
NO	2.29±0.25	BLACK	5787745-2
NO	2.84±0.25	BLACK	5787745-1
HIGH TEMPERATURE COMPATIBLE	D	HOUSING COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN LEO ZHOU 26OCT2004	 TE Connectivity							
DIMENSIONS: mm		CHK STEVEN YAO 26OCT2004								
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD JENOMOTO 26OCT2004	NAME RECEPTACLE ASSEMBLY, RIGHT ANGLE, STACKED, THRU-HOLE, USB						
	0 PLC ±		PRODUCT SPEC							
	1 PLC ± 0.35		APPLICATION SPEC							
	2 PLC ± 0.25									
	3 PLC ± 0.15									
4 PLC ±		SIZE A1		CAGE CODE 00779	DRAWING NO 5787745	RESTRICTED TO —				
ANGLES ± °		FINISH —		WEIGHT —		CUSTOMER DRAWING		SCALE 1:1	SHEET 1 of 1	REV A2
MATERIAL —										