

**MODEL:** PJ-005A | **DESCRIPTION:** DC POWER JACK**FEATURES**

- 2.0 mm center pin
- mounting hardware includes nut and washer
- panel mount

**SPECIFICATIONS**

| parameter                  | conditions/description | min | typ   | max | units  |
|----------------------------|------------------------|-----|-------|-----|--------|
| rated input voltage        |                        |     | 24    |     | Vdc    |
| rated input current        |                        |     |       | 5   | A      |
| contact resistance         |                        |     |       | 30  | mΩ     |
| insulation resistance      | at 500 Vdc             | 100 |       |     | MΩ     |
| voltage withstand          | for 1 minute           |     |       | 500 | Vac    |
| insertion/withdrawal force |                        | 0.3 |       | 3   | kg     |
| operating temperature      |                        | -40 |       | 70  | °C     |
| life                       |                        |     | 5,000 |     | cycles |
| flammability rating        | see material table     |     |       |     |        |
| RoHS                       | yes                    |     |       |     |        |


**SOLDERABILITY**

| parameter      | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for 3~5 seconds        | 285 |     | 305 | °C    |

MECHANICAL DRAWING

units: mm  
olerance:  
X.X ±0.50 mm  
X.XX ±0.30 mm  
X.XXX ±0.15 mm  
unless otherwise specified

| ITEM | DESCRIPTION             | MATERIAL      | PLATING/COLOR |
|------|-------------------------|---------------|---------------|
| 1    | housing                 | PBT [UL94V-0] | black         |
| 2    | center pin terminal [1] | copper alloy  | silver        |
| 3    | tip spring [2]          | copper alloy  | silver        |
| 4    | shunt spring [3]        | copper alloy  | silver        |
| 5    | bushing                 | copper alloy  | nickel        |
| 6    | center pin              | copper alloy  | nickel        |
| 7    | washer                  | bakelite      | ---           |
| 8    | nut                     | copper alloy  | nickel        |
| 9    | washer                  | Q195          | nickel        |



REVISION HISTORY

| rev. | description                            | date       |
|------|----------------------------------------|------------|
| 1.0  | initial release                        | 01/30/2006 |
| 1.01 | applied new spec template              | 05/06/2011 |
| 1.02 | updated voltage and current rating     | 07/09/2014 |
| 1.03 | removed slot from threaded barrel      | 09/01/2017 |
| 1.04 | brand update                           | 10/30/2019 |
| 1.05 | updated hand soldering recommendations | 02/24/2022 |
| 1.06 | logo, datasheet style update           | 08/05/2022 |
| 1.07 | CUI Devices rebranded to Same Sky      | 09/12/2024 |
| 1.08 | factory location change                | 04/29/2026 |
| 1.09 | updated drawing                        | 05/27/2026 |

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**sameskydevices.com**