









1. MATING PART NO.; 176143
2. THIS PRODUCT CONSISTS OF A PLUG HOUSING,
A SEAL RING AND A KEYING
3. PRODUCT SPECIFICATION; 108-5294
APPLICATION SPECIFICATION; 114-5126
CUSTOMER MANUAL; 412-5488
4. APPLIED CONTACTS

RECEPTACLE	CONTACT P/N	WIRE RANGE (mm ²)	INSULATION DIA
	175090	0.5~1.25	ø2.0~ø2.6
	175091	2~3	ø2.9~ø3.8

1. 嵌合相手品番：176143
2. 本製品はプラグハウジングとキーイング、
シールリングから構成されている。
3. 製品規格：108-5294
圧着規格：114-5126
取扱説明書：412-5488
4. 適用端子型番

リセプタクルコンタクト P/N	ワイヤーレンジ (mm ²)	被覆外径
175090	0.5~1.25	ø2.0~ø2.6
175091	2~3	ø2.9~ø3.8

黒 BLACK	淡灰 LIGHT GRAY	淡灰 LIGHT GRAY	6-176146-6
	濃灰 DARK GRAY	濃灰 DARK GRAY	176146-6
	黒 BLACK	黒 BLACK	176146-2
SEAL RING COLOR シールリング色	KEYING COLOR キーイング色	HOUSING COLOR ハウジング色	PARTS NO. 型番

WIRE RANGE SEE TABLE	THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Y.KINOSHITA 12NOV91	 TE Connectivity			
INSULATION DIA SEE TABLE	DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 	CHK Y.KINOSHITA 12NOV91				
TOLERANCE UNLESS OTHERWISE SPECIFIED: 一般公差 0 < ≤ 10 : ±0.2 10 < ≤ 30 : ±0.25 30 < ≤ 100 : ±0.3 ANGLE : ±3° 角度		0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± ±	APVD S.ISOHATA 12NOV91	NAME			
			PRODUCT SPEC 108-5294	187 SERIES SEALED CONNECTOR 2POSITION PLUG HOUSING ASSY			
			APPLICATION SPEC 114-5126				
			WEIGHT 8.0 g				
			MATERIAL PBT	FINISH SEE TABLE	CUSTOMER DRAWING		