

Jun.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	_____	_____	_____	_____	
	_____	_____	_____	_____	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
MECHANICAL CHARACTERISTICS					
VIBRATION	FREQUENCY: 10 TO 55 Hz (1CYC, 5min), SINGLE AMPLITUDE 0.75 mm, AT 10 CYC, FOR 3 DIRECTIONS.		NO SEPARATION FROM APPLICABLE CONNECTOR.	X	-
SHOCK	IN OPPOSITE DIRECTIONS OF EACH 3 DEMENSION ALAXIS FOR 3 TIMES AT 490 m/s <sup>2</sup> DURATIONS OF PULSE 11 ms.		NO SEPARATION FROM APPLICABLE CONNECTOR.	X	-
ENVIRONMENTAL CHARACTERISTICS					
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ R/T <sup>(1)</sup> → +85 → R/T °C TIME 30 → 10 TO 15 → 30 → 10 TO 15 min UNDER 5 CYCLES.		NO DAMAGE, CRACK OF PARTS.	X	-
DRY HEAT	EXPOSED AT + 85 °C , 96 h.		NO DAMAGE, CRACK OF PARTS.	X	-
COLD	EXPOSED AT - 55 °C , 96 h.		NO DAMAGE, CRACK OF PARTS.	X	-
SEALING <sup>(2)</sup>	EXPOSED AT A DEPTH OF 1 m FOR 0.5 h.		NO WATER PENETRATION INSIDE CONNECTOR.	X	-
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
①					
REMARK			APPROVED	HY. KOBAYASHI	18.03.16
NOTES (1) R/T : ROOM TEMPERATURE			CHECKED	HY. KOBAYASHI	18.03.16
(2) SEALING SHALL BE TESTED BY APPLICABLE CONNECTOR.			DESIGNED	DS. MATSUNE	18.03.16
Unless otherwise specified, refer to IEC 60512.(JIS C 5402)			DRAWN	DS. MATSUNE	18.03.16
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-112274-31-00
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	HR30-6R-C (31)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL130-3001-0-31	1/1