




REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
A	PROPOSAL	AUG09/21	L.CHAN



RECOMMENDED PANEL CUTOUT


MATERIALS:

HOUSING: ENGINEERING THERMOPLASTIC
FLAMMABILITY RATING UL 94V-0
COLOR: YELLOW, PANTONE #114C

CONTACTS: PHOSPHOR BRONZE
PLATING: GOLD ON MATING SURFACES
(SEE PART NO. FOR THICKNESS).
50 μ " [1.27 MICRONS]
MIN. NICKEL UNDERPLATE
100 μ " [2.54 MICRONS]
MIN. MATTE TIN ON CONTACT TAILS.

PART NUMBER: RJHSE-X080-010-4

GOLD PLATING
E=RJ45 FLAT CONTACT 6u"
G=RJ45 FLAT CONTACT 15u"
J=RJ45 FLAT CONTACT 30u"
5=RJ45 FLAT CONTACT 50u"



RECOMMENDED P.C.B. LAYOUT
(COMPONENT SIDE OF BOARD)



UNLESS SPECIFIED OTHERWISE		DRAWN	W.QIU	DATE	AUG09/21	Amphenol Canada Corp. Commercial Products	
PRIMARY UNITS	INCH	CHECKED	L.CHAN	DATE	AUG09/21		
SECONDARY	MILLIMETER	M.E. APP'D				TITLE SINGLE-PORT HIGH SPEED RJ45, MODULAR JACK, 8P8C, UNSHIELD, WITHOUT LEDS, YELLOW HOUSING, TRAY PACKAGING, -RoHS COMPLIANT	
REFERENCE IN PARENTHESES		Q.A. APP'D					
GENERAL TOLERANCES		DWG APPR.				DWG. NO. P-RJHSE-X080-010-4	
1 DECIMAL PLACE	±0.025	ENG. REL. NO.					
2 DECIMAL PLACES	±0.020	REF.				CODE ID NO. 03554 DWG SIZE: c SCALE: N/A SHEET 1 OF 1	
3 DECIMAL PLACES	±0.015	THIRD ANGLE PROJECTION					
ANGULAR DEGREES	±1.0°	DO NOT SCALE DRAWING					