

Δ COUNT		REVISIONS		BY	CHKD	DATE	Δ COUNT		REVISIONS		BY	CHKD	DATE
Δ							Δ						
Δ							Δ						

APPLICABLE STANDARD													
RATING	VOLTAGE	CONTACT No. / ~ *	AC 250 V			APPLICABLE CABLES							
	CURRENT	CONTACT No. / ~ *	3 A			IMPEDANCE FREQUENCY RANGE		Ω (0 ~ Hz)					
	POWER					OPERATING TEMPERATURE RANGE		- 35 °C ~ + 85 °C (Notes:1)					
	SPECIALTY												

SPECIFICATIONS

No.	ITEM	CONDITIONS	TEST STANDARD	MIN	MAX	UNITS	QT.	AT
1	DESIGN-MATERIAL-FINISH	ADC Applicable std. and DC 3-160094-02		—	—	—	○	○
2	MARKING			—	—	—	○	○
3	INSULATION RESISTANCE	Must be over standard value at DC 500V.	MIL-STD-1344	1000	—	MΩ	○	—
4	CONTACT RESISTANCE UNIT CONTACT	The voltage drop must be under the Std. value at DC 0.1 A.	MIL-STD-1344	—	30	mΩ	○	—
	CONTACT	The voltage drop must be under the Std. value at DC A.		—	—	mΩ	—	—
5	DIELECTRIC WITHSTANDING VOLTAGE	Must withstand AC DC 650V for one minute.	MIL-STD-1344	—	—	—	○	—
6	LOW LEVEL CIRCUIT	The Contact Resistance must be under the Std. value at DC20mV less and mA.		—	—	mΩ	—	—
7	DRY CIRCUIT	Must have conductivity in alternate current at DC μV.		—	—	—	—	—
8	CONTACT ENGAGEMENT AND SEPARATION FORCES	Must be suitable for the Std. value at applicable gauge. gauge size		—	—	gf	—	—
	MATING AND UNMATING FORCES	Must be suitable for the Std. value.		—	—	kgf	—	—
9	HUMIDITY	Insulation resistance must be over the Std. value at - 40±2°C 90 ~ 95 %, 96 hours.	MIL-STD-1344	1000	—	MΩ	○	—
		at high humidity after high humidity						
10	VIBRATION	Must have no damage, crack and looseness of parts at Frequency range 10 ~ 55 Hz, amplitude 0.75mm, —G at 2 hours for 3 directions.	MIL-STD-1344	—	—	—	○	—
11	SHOCK	Must have no damage, crack and looseness of parts after 3 cycles at 490m/s ² in 3 directions.	MIL-STD-1344	—	—	—	○	—
12	TEMPERATURE CYCLING	Must have no damage, crack and looseness of parts for -55 ~ +85°C, 5 cycles.	MIL-STD-1344	—	—	—	○	—
13	DURABILITY UNIT CONTACT	Must be less than the Std. value after 30 insertion and extraction cycles at the condition described in above item No.4.	MIL-STD-1344	—	30	mΩ	○	—
	CONTACT			—	—	mΩ	—	—
14	SALT SPRAY (CORROSION).	Must not have heavy corrosion after salt water spray for hours.		—	—	—	—	—
15	H ₂ S-EXPOSURE	Must not have heavy corrosion after ppm for hours.		—	—	—	—	—
16	SO ₂ -EXPOSURE	Must not have heavy corrosion after ppm for hours.		—	—	—	—	—

Notes:1
This temperature includes a rise by heat's generation of connector when electricity passes.

REMARKS	APPROVED	<i>H. Yamamoto</i>	94.3.25	ISSUED BY
	REVIEWED			
	CHECKED	<i>J. Oma</i>	94.3.25	
	DESIGNED	<i>M. Gotoh</i>	94.3.24	
	DRAWN	<i>M. Gotoh</i>	94.3.24	

DRAWING No.	SLC4-160094-02		SPECIFICATION SHEET	PART No.	DF1B- * DES-2.5RC
				CODE No.	0346 1 CL 541-0362-8-

NOTE QT:Qualification Test AT:Assurance Test O:Applicable item FORM No.

TO